

elegant lighting

Balto II

Flush Mount 4CCT

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
	2700K/3000K/3500K/4000K	BK Black WT White	13.2W	1125	615

DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted interior diffuser BALTO II blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW704605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K,3000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum body with interior frosted PC diffuser

FINISHES:



LINE DRAWING

