

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:





I-Beam

WS-94620

PRODUCT DESCRIPTION

With a nod to architecture, this clever sconce brings the functional forms of construction to modern décor in a low profile and a sleek, versatile finish. LEDs are positioned both toilluminate the wall surrounding the sconce and to minimize glare from any angle. That means this sconce looks beautiful from both the front and side—making it ideal for corridors andstairwells.

FEATURES

- \bullet Driver installed within the Junction Box, driver dimension: 2.8" x 1.3" x 1.2"
- Acrylic diffuser

SPECIFICATIONS

Rated Life 50,000 Hours

Standards ETL, cETL, Damp Location Listed

Input 120-277 VAC,50/60Hz

Driver Dimension 2.8" x 1.3" x 1.2"

Dimming ELV: 100-10%,TRIAC: 100-10%

Mounting Can be mounted on wall in all orientations

Color Temp 3000K CRI 90

Construction Aluminum body with acrylic diffuser

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-94620 20"	3000K	AL Brushed Aluminum	32.3W	1311	1160
	3000K	WT White	32.3W	1311	1160

