## **PRODUCT FEATURES**

- · Field-changeable optics for ultimate customization
- · Advanced LED technology
- Modest size profile to minimize bulky appearance
- Compatible with the Monorail and Monopoint systems by Tech Lighting
- · Integrated fully dimmable LED lamp
- Protected by a 5-year warranty



Includes 7 watt, 647.5 delivered lumens, 2700K or 3000K, 90 CRI field replaceable LED module Dimmable with most LED compatible ELV and Triac dimmers. Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.



Clear Black Finish









Clear Black Finish

Transparent Smoke Black Finish

Clear Satin Nickel Finish

Transparent Smoke Satin Nickel Finish

To view all available finish options, please visit techlighting.com

#### ORDFRING INFORMATION

700	SYSTEM	BRM COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
	FJ FREEJACK	<b>927</b> 90 CRI 2700K	<b>20</b> 20°	<b>05</b> 5"	C CLEAR	B MATTE BLACK
	MP MONOPOINT	930 90 CRI 3000K	<b>30</b> 30°	<b>08</b> 7.76"	<b>K</b> TRANSPARENT SMOKE	S SATIN NICKEL
	MO MONORAIL		<b>40</b> 40°	<b>14</b> 13.76"		
	MO2 TWO-CIRCUIT MONORA	IL				


Note. MP includes 4 Round Flush Canopy. Matte Black Finish option ships with Satin Nickel Stem. 4" Stem length not available on WMO System option.

700	BRM
JOB NAME	
NOTES	



## **SPECIFICATIONS**

HARDWARE MATERIAL	Metal			
SHADE MATERIAL				
NET WEIGHT	0.79 lbs			
HEIGHT	4.8in			
WIDTH	1.3in			
LENGTH	3in			
BEAM SPREAD				
UP LIGHT / DOWN LIGHT / BOTH?				
WET LISTED				
DAMP LISTED				
DRY LISTED				
MIN. HANGING HEIGHT				
MAX HANGING HEIGHT				
TOTAL CORD LENGTH				
SLOPED CEILING ADAPTABLE?				
GENERAL LISTING				
INCLUDES				



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
	Clear, Transparent Smo	oke : 680		
DELIVERED LUMENS	Transparent Smoke, Cl	ear:		
	647.5			
WATTS	7			
MAX WATTAGE PER BULB	7W			
INPUT VOLTAGE	12V			
INPUT VOLTAGE	120V			
DIMMING TYPE*				
	Clear, Transparent Smo	oke :		
ССТ	2700K			
CCI	Clear, Transparent Smo	oke :		
	3000K			
CRI	90 CRI			
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?	Υ			
WARRANTY**			<u> </u>	

<sup>\*</sup> Dimming information available at <a href="www.techlighting.com/Downloads#dimming">www.techlighting.com/Downloads#dimming</a> \*\* Visit techlighting.com for specific warranty limitations and details.

# T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6.		No	
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.	I	Yes	

<sup>\*</sup>If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

