



Location:	Project:		
	Location:		

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



0 to 60

PRODUCT DESCRIPTION

An exquisite sense of simplicity that lends to its surroundings an even layer of energy-efficient illumination. This clean design blends Euro styling and functional technology suitablefor flattering illumination. ADA Compliant. 3 CCTs are selectable to create the white light color temperature of your choice. Like a fast race car, this clean design is a versatileoption that can be installed vertically, horizontally, or in any orientation.

FEATURES

- ACLED driverless technology
- Adjustable backplate offers flexible mounting and accommodates to off-center junction box locations
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Conversion plate included to accommodate 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

Rated Life	60000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV: 100-10%,TRIAC: 100-10%
Mounting	Can be mounted on wall in all orientations
Color Temp	3000K,3500K,2700K
CRI	90
Construction	Extruded aluminum body with etched acrylic diffuser

REPLACEMENT PARTS

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
O 37"	○ 2700K○ 2700K○ 3000K○ 3000K○ 3500K○ 3500K	O BK Black O BN Brushed Nickel O BK Black O BN Brushed Nickel O BK Black O BN Brushed Nickel	16.3W 16.3W 16.3W 16.3W 16.3W	958 958 1158 1158 1087 1087	702 702 774 774 750 750

