



Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
○ 6"	○ 2700K	○ BK Black	10.3W	878	574
	○ 2700K	○ SS Stainless Steel	10.3W	878	574
	○ 3000K	○ BK Black	10.3W	790	574
	○ 3000K	○ SS Stainless Steel	10.3W	790	574
	○ 3500K	○ BK Black	10.3W	800	574
	○ 3500K	○ SS Stainless Steel	10.3W	800	574

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Pi

PRODUCT DESCRIPTION

This brand-new design in durable stainless steel handles the outdoor elements with ease, while the sleek polished hardware also gives interiors a welcome touch of industrial refinement. A user-friendly twist lock mechanism makes installation a snap. As for illumination, the finely crafted diffuser enhances the brightness for a beautiful mix of task and ambient light.

FEATURES

- ACLED driverless technology
- Weather-resistant 316 stainless steel body
- Lightweight injection-molded acrylic diffuser enhances brightness
- Easy twist-lock installation prevents slippage with no visible hardware
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Compact 3CCT switch installs within the junction box
- 277V option available for 9", 12" and 15" only (special order), not available for 6"
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL, Wet Location Listed, IP65, Title 24 JA8: 2019 Compliant, Energy Star 2.0, ADA
Input	120 VAC, 50/60Hz
Dimming	ELV: 100-10%, TRIAC: 100-10%
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3500K, 3000K, 2700K
CRI	90
Construction	Weather-resistant 316 stainless steel body with acrylic shade