

# elegant lighting

## Edge Round Large LED Surface Mount Disc Light EGRF Series

|                |  |              |
|----------------|--|--------------|
| LOCATION       |  | DATE         |
| PREPARED BY    |  | QUANTITY     |
| COMMENTS       |  | FIXTURE TYPE |
| CATALOG NUMBER |  |              |

### Features

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed.

Indoor use only - Wall or ceiling mount.

Outdoor use only - Covered ceiling mount.



### Construction

Edge-lit technology housing is injection molded with steel backplate.

Twist and lock bracket.

Mounts to standard junction box (not included).

Power supply connections must be made inside junction box.

### Finish

White or Black finish.

### Diffuser

White acrylic diffuser.

### Electrical

#### D1 Driver

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

#### D2 Driver

Input 120-277 VAC 60 Hz. LED driver is dimmable with 0-10V dimmer.

### Lamping

Integrated LED modules capable of producing:

25W = 2525 delivered lumens

40W = 3375 delivered lumens

Adjustable Choice 3000K, 4000K, 5000K (CCT). Preset at 3000K.

Rated for 50,000 Hrs. 90 CRI.

### Certification

cETLus listed

ENERGY STAR® Qualified

Title 24/JA8 Compliant

Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use).

Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

### Specifications and dimensions

subject to change without notice.

### Ordering Information:

White | Black | LED | <sup>Delivered</sup> Lumens | Adjustable CCT | DIA. | D

EGRF2440LAJD2WH | EGRF2440LAJD2BK | 40W 3375 3000K/4000K/5000K | 23-5/8" 1"

