LEDGE - model: FM-14

LED Flush Mount





Fixture Type:	
Catalog Numbe	r:
Project:	
110,000	
Location:	

PRODUCT DESCRIPTION

A luminous architectural profile and superior construction make this ceiling flush mount or wall sconce appropriate for transitional and contemporary interiors or exteriors. Mitered silk-screened glass encases a maximum number of LEDs engineered for optimal illumination. Allows for cohesive specifications across residential and commercial interior and exterior applications.

FEATURES

- Wet location listed, IP65 rated
- · CEC Title 24 compliant
- · Also rated for use in closets
- · Dimming with electronic low voltage (ELV) dimmer
- · No transformer or driver required
- 50,000 hour rated life
- · Color Temp: 3000K
- · CRI: 90

SPECIFICATIONS

Construction: Aluminum with mitered silk-screened glass

Light Source: High output LED

Dimming: Dims to 10% with an electronic low voltage (ELV) dimmer

Mounting: Mounts directly to junction box

Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH)

Standards: ETL & cETL listed.

			LED	Delivered			
	Wattage	Voltage	Lumens	Lumens	Finish		
					AL	Brushed Aluminum	
FM-1410	17W	120V	1104	750	ВК	Black	
FM-1414	38W	120V	2772	1475	BZ	Bronze	
					GH	Graphite	

Example: FM-1414-AL