

Custom 36"w x 48"h



PRODUCT DESCRIPTION

A singularly smart and modern alternative to bathroom sconces, Novo™ pairs incredible natural-looking illumination with ultra-soft wall glow, forming a harmonious combination of task and ambiance lighting.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as left and right-side wall-glow ambient lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with a greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on left and right side with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliance available
- 10-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Ava™ Technology ^{1, 2}
- Keen™ Technology ²
- Polaris™ Technology ^{1, 2}
- Seamless™ Technology ^{1, 2}
- Vive™ Technology ^{1, 2}
- Defogger
- CCT: 2,700K
- 0-10V dimming
- Forward-phase dimming
- 277V available ³
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 60 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ Minimum order quantity required

² See technology specification sheets for more details

³ May not be compatible with all upgrades and options

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

| Base Model* | Dimensions | Power Requirements |
|-----------------------------|---|--------------------|
| NOV2-24.00x36.00-L7CSHD-30K | 24"W x 36"H x 1.75"D (610mm x 914mm x 44mm) | 120/240 VAC, 56W |
| NOV2-36.00x36.00-L7CSHD-30K | 36"W x 36"H x 1.75"D (914mm x 914mm x 44mm) | 120/240 VAC, 56W |
| NOV2-48.00x36.00-L7CSHD-30K | 48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm) | 120/240 VAC, 56W |
| NOV2-60.00x36.00-L7CSHD-30K | 60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm) | 120/240 VAC, 56W |

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

NOV2-36.00x48.00-CC2-L7CSHD-30K-M

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

