



UNDERWATER LIGHTS SL-51-ST SERIES

SL-51-ST-BAV
as displayed
not for underwater use

SPECIFICATIONS

CONSTRUCTION: Cast brass base & starfish top; Brass nickel-plated liquid tight straight bushing.

LENS: High impact clear tempered acrylic

LAMP SUPPLIED: 20w MR16 ULTRA FL(BAB); 10,000 hours average rating (50w max.)

LAMP OPTIONS: We recommend 35w MR16 TITAN 18,000 hours average rating or 4w ARROW LED 50,000 average rating or 4w or 2w LED Panel; 50,000 hours average rating

SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

Note: Led panel models require no socket. LED is hard wired inside fixture

GASKET: High temperature black silicone

12v EXTERNAL DRIVER For Led Panel Models Only: 4w 350mA output, 12v AC input. Voltage range of 9 to 18 volts with optimum operating range of 10 to 15 volts for consistent performance and brightness. For use with magnetic transformers only.

WIRING: 15 feet 18/2 SJTOW cord (available up to 50 feet)

MOUNTING: None

FINISH: Unfinished brass.

Optional finishes: Black Acid Treatment (-BAT) & Brass Acid Rust (-BAR) Brass Acid Verde (-BAV)




SL-51-ST-BAT

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP SUPPLIED	SHIP WEIGHT
SL-51-ST-BRS	Cast Brass Underwater Starfish Light	20w Ultra FL(BAB)	3.0 lbs

LIGHT DISTRIBUTIONS



UL 676

IP68

CE



ACCESSORIES

ADDITIONAL SJTOW CORD Sold in 5 foot lengths, not to exceed total of 50 feet.
Add total number of feet to catalog number.

JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

FOCUS INDUSTRIES INC.
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT