



DEMOLITION LANDFILL

Acceptable Wastes

- Bituminous concrete (includes asphalt pavement and blacktop)
- Concrete (including rebar)
- Stone
- Uncontaminated soil
- Masonry (bricks, stucco and plaster)
- Untreated wood (including painted, stained and/or varnished dimensional lumber, pallets, tree stumps, grubbing, root balls, particle board, plywood, fencing and dock materials)
- Siding (Includes vinyl, masonite, untreated wood, aluminum and steel.)
- Wall coverings
- Electrical wiring and components
- Roofing materials
- Duct work
- Wall board, sheet rock
- Built-in cabinetry
- Plumbing fixtures
- Affixed carpet and padding
- Ceramic items
- Conduit and pipes
- Glass (limited to window and door glass from buildings and structures) and Caulk* material.
- Insulation (Includes fiberglass, mineral wool, cellulose, polystyrene and newspaper.)
- Plastic building parts
- Sheathing
- Molded fiberglass
- Rubber
- Drain tile
- Recognizable portions of burned structures
- Metal
- Ceiling tile
- Wood and vinyl flooring
- Asbestos-containing materials (acceptance of non-friable asbestos waste is addressed in the Facility ISWMP)

* Caulk material must contain less than 50 ppm PCB's as determined by composite laboratory test samples and/or not be from pre-1979 era structures and must not be separated from the structure and deposited in bulk form.