

LITHIUM

ALPHA 50-60 Li
5,000 - 6,000 lbs. Capacity
Li-ion Pneumatic Forklift

LPG

ALPHA 50-60 LPG
5,000 - 6,000 lbs. Capacity
LPG Pneumatic Forklift



Why choose between price and quality **WHEN YOU CAN HAVE BOTH!**



HIGHLIGHTS

- ▶ Powerful high quality permanent magnet motor
- ▶ 4-Way proportional hydraulics to carriage
- ▶ On-demand fully hydrostatic power steering (FHPS)
- ▶ Integrated side shift
- ▶ Intelligent buffering
- ▶ Multi-function Eye-Level LCD Display: lifting weight, lifting height, speed, power, steering, fault code, alarm, fuel indicator and more
- ▶ Deluxe suspension seat
- ▶ Operator presence sensing system
- ▶ LED Safety Blue light, rear work light, headlights, and strobe
- ▶ Rear grab bar with horn
- ▶ Tilt cylinder boots
- ▶ Automatic speed reduction in turns
- ▶ CAN-bus communications system
- ▶ On-board self-diagnostics
- ▶ Lithium battery with REMA connector provides multiple shift operation
- ▶ Integral 110V built-in charger (external charger optional)
- ▶ Fast charging 2-3 hours

ALPHA 50-60 Li **5,000 - 6,000 lbs. Capacity** Li-ion Pneumatic Forklift

The ALPHA Li Series are highly efficient, durable Lithium forklifts. They are designed for indoor and outdoor applications. The mast system, front/rear axles and chassis are engineered to be tough like an Internal Combustion forklift, but with all the advantages of Lithium. A permanent magnet motor is used to achieve high performance with low operating and maintenance costs. Greatly increase your work productivity with these quiet, very low maintenance, ultra-smooth, lithium forklifts.

HIGHLIGHTS

- ▶ Powerful Kubota engine 56.2 HP/2,600 rpm
- ▶ 4-Way hydraulics to carriage (proportional hydraulics - optional)
- ▶ On-demand fully hydrostatic power steering (FHPS)
- ▶ Integrated side shift
- ▶ Intelligent buffering
- ▶ Multi-function Eye-Level LCD Display: lifting weight, lifting height, speed, power, steering, fault code, alarm, fuel indicator and more
- ▶ Deluxe suspension seat
- ▶ Operator presence sensing system
- ▶ LED Safety Blue light, rear work light, headlights, and strobe
- ▶ Rear grab bar with horn
- ▶ Tilt cylinder boots
- ▶ Swing-out LPG tank
- ▶ Meets EPA Tier 2 / CARB Tier 3 and EU Stage V emission regulations for engine exhaust emissions




The ALPHA LPG Series is the same forklift but with a Kubota LPG engine, allowing you to choose the power source that best fits your operation without sacrificing performance, comfort or familiarity. This minimizes spare parts inventory, reducing service and maintenance costs.

Future lithium conversion kits will present the opportunity for ALPHA LPG forklifts to be upgraded to lithium power, extending their operational lifespan.

ALPHA 50-60 LPG
5,000 - 6,000 lbs. Capacity
LPG Pneumatic Forklift

GREAT VISIBILITY. ERGONOMIC.



Mast layout is optimized for a wide view and clear visibility while operating.



The large, ergonomic cab and user-friendly design ensures operator comfort throughout the entire work shift. Low entrance height provides operator easy and safe access.




Deluxe suspension, fully adjustable seat reduces vibration to the driver to effectively reduce driver fatigue for all sizes of operators.

On-Demand Fully Hydrostatic Power Steering (FHPS) guarantees smooth steering, preventing over-run and kick-back. Spinner knob allows easier one-handed steering.

SUPERIOR DESIGN AND PERFORMANCE



Heavy-duty steel chassis, axles, mast and overhead guard deliver high strength and stability for high lifting heights and heavy loads.



Integrated side shift allows for precise movement of the fork carriage without having to move the whole forklift.



Intelligent buffering effectively protects the ground and cargo from damage while forks descend to the ground.



Operator Presence System (OPS) — When operator is not in seat, the hydraulic lift and tilt controls automatically lock out and traveling is disabled.



Large frame-mounted LCD display improves safety and efficiency by placing the screen in the operator's line of sight.



Cast axles increases the bearing load and improves the truck structure, while prolonging vehicle service life.



Travel Speed Up To 12.4 mph



Gradeability / Full Load

UP TO 20%



Fast Lifting Speed Up To 118 ftn

SUPERIOR DESIGN AND PERFORMANCE



Tilt cylinder boots protect tilt cylinder and oil seals from the environment, prolonging cylinder life.



An enlarged step allows the operator to safely and easily get on and off the forklift.



Adjustable steering column to ensure operator comfort throughout the entire shift.

A LED headlights brighten dimly lit areas for optimal visibility.

B Panoramic rear-view mirror gives the operator a wider rear visibility.

C Frame-mounted LCD display mounted in the operator's line of sight.

D LED signal lights improve safety, last a long time and are very durable.

E LED rear work light provides excellent visibility while backing up.

F LED strobe flashes while operating the vehicle to alert others in the area.

G Blue LED light projects a blue beam onto the floor to warn pedestrians.

H Rear grab bar with horn provides easy horn operation while traveling in reverse.

I Dual wide angle mirrors (optional - not shown).



SUPERIOR DESIGN AND PERFORMANCE



Large diameter, solid pneumatic tires ensure comfortable driving for outdoor and indoor use.



Optimized pedal position gives operator comfort throughout the entire work shift while reducing operator fatigue.



USB connector for charging and powering of additional devices during operations.



Cup and Pen holder provide convenience for operator.



Gain rapid access to engine and other components with an air spring assisted engine cover and integrated hood lock. Hood opens 80 degrees to allow for complete access.

Modular frame is designed based on the same chassis as the NOBLELIFT LPG, Diesel and Electric forklifts. Main components and configurations are the same. Spare parts inventory is minimized to reduce service and maintenance costs.



APPLICATIONS



Manufacturing and Production
Building Materials and Construction Supply
Warehousing, Distribution and Logistics
Lumber, Metal and Heavy Industrial Products
Freight Terminals and Cross-Docking


ALPHA Li ADVANTAGES



Automatic decelerating while turning, improves safety and stability, while preventing product damage.



Battery allows for multiple shift operation.



Easily check truck's condition and troubleshoot with CAN-bus technology.

LONG LASTING AND SAFE LITHIUM POWER

NOBLELIFT uses LiFePO4 chemistry, the longest lasting and safest lithium battery chemistry available. Our lithium batteries are equipped with a Battery Management System (BMS), thermal management system, and an automotive-grade DC high-voltage control system. BMS manages charging and discharging data to ensure safety throughout its life cycle.

ALPHA 50-60 Li forklifts have a 10 year or 20,000 hour warranty on the on the lithium battery cells.



ADVANTAGES OF LITHIUM POWER

76.8 VOLT



Fast-charging maintenance-free Lithium battery can be fully charged in 2-3 hours. Battery can be opportunity charged during user breaks and during shift changes which allows the truck to run continuously through multi-shift operations. No battery changes are necessary.

TOTAL COST OF OWNERSHIP

UP TO
47%
SAVINGS OVER 5 YEARS


Opportunity Charging
Increases Productivity



Lead-Acid Battery
Acquisition Cost



Internal Combustion
Acquisition Cost



LITHIUM BATTERY ADVANTAGES

Lead-Acid Battery

Lower fleet availability -
Work is interrupted because
battery needs to be fully
charged before next use

Periodic battery replacement

Outsourced or in-house
maintenance personnel
required

8-10 Hours - 2 or more
batteries per lift truck

Build an expensive battery
room with ventilation

Releases hydrogen while
charging - Can result in
explosion - Acid burns can
happen during maintenance

Power loss

Lithium Battery

100% Fleet availability -
Opportunity charging allows
battery to be charged in
between use

Batteries last 3 times longer
and do not need to be
replaced

No maintenance cost

2-3 Hours - 1 Battery per
lift truck

No battery room needed

No dangerous substances

No power loss - Reduces
energy consumption by 35%

**Productivity -
Memory Effect**



**Service
Life**



**Ongoing
Maintenance**



**Charge
Duration**



**Battery
Room**







**Dangerous
Substances**



**Power
Savings**




Mast Table ALPHA 50-60 Li												
Designation	Lift height h3 (in)		Free lift h2 (in)		Closed mast height h1 (in)		Extended mast height h4 (in)		Tilt forward / backward a/b (°)		Capacity table (lb) C=24in without attachment	
	ALPHA 50 Li	ALPHA 60 Li	ALPHA 50 Li	ALPHA 60 Li	ALPHA 50 Li	ALPHA 60 Li	ALPHA 50 Li	ALPHA 60 Li	ALPHA 50 Li	ALPHA 60 Li	ALPHA 50 Li	ALPHA 60 Li
Two-stage ZT	79	79	5.5	5.7	64	61	120	122	6 / 12	6 / 12	5,000	6,000
	98	98	5.5	5.7	69	71	140	142	6 / 12	6 / 12	5,000	6,000
	106	106	5.5	5.7	73	75	147	150	6 / 12	6 / 12	5,000	6,000
	118	118	5.5	5.7	79	81	159	162	6 / 12	6 / 12	5,000	6,000
	130	130	5.5	5.7	84	87	171	173	6 / 12	6 / 12	5,000	6,000
	138	138	5.5	5.7	88	91	179	181	6 / 12	6 / 12	5,000	6,000
	142	142	5.5	5.7	92	95	183	185	6 / 12	6 / 12	5,000	6,000
	146	146	5.5	5.7	94	97	187	189	6 / 12	6 / 12	5,000	6,000
	150	150	5.5	5.7	96	99	191	193	6 / 12	6 / 12	5,000	6,000
	157	157	5.5	5.7	102	105	199	201	6 / 12	6 / 12	5,000	6,000
	169	169	5.5	5.7	108	110	210	213	6 / 6	6 / 6	4,620	6,000
	177	177	5.5	5.7	112	114	218	221	6 / 6	6 / 6	4,400	6,000
	189	189	5.5	5.7	118	120	230	232	6 / 6	6 / 6	3,960	5,940
	197	197	5.5	5.7	122	124	238	240	6 / 6	6 / 6	3,740	5,610
	217	217	5.5	5.7	132	134	258	260	3 / 6	3 / 6	3,300	4,950
	236	236	5.5	5.7	142	144	277	280	3 / 6	3 / 6	2,530	3,410
Two-stage FFL	98	98	30	33	71	78	140	143	6 / 12	6 / 12	5,000	6,000
	106	106	34	37	75	82	147	150	6 / 12	6 / 12	5,000	6,000
	118	118	38	41	79	86	159	162	6 / 12	6 / 12	5,000	6,000
	130	130	44	49	85	94	171	174	6 / 12	6 / 12	5,000	6,000
	142	142	50	55	91	100	183	186	6 / 12	6 / 12	5,000	6,000
Three-stage FFL	157	157	59	63	101	108	199	202	6 / 12	6 / 12	5,000	6,000
	157	157	36	38	77	83	199	202	6 / 6	6 / 6	4,840	5,940
	169	169	40	42	81	82	211	213	6 / 6	6 / 6	4,620	5,720
	177	177	43	44	84	86	221	223	6 / 6	6 / 6	4,290	5,280
	189	189	46	48	88	94	231	233	6 / 6	6 / 6	4,070	5,060
	197	197	49	51	90	96	238	241	6 / 6	6 / 6	3,740	4,730
	217	217	56	57	97	103	258	261	3 / 6	3 / 6	2,860	3,630
	236	236	64	64	105	109	278	280	3 / 6	3 / 6	1,870	2,640



Identification				
1.1	Manufacturer		NOBLELIFT	
1.2	Model		ALPHA 50 Li	ALPHA 60 Li
1.3	Drive (electric – battery or mains, diesel, petrol, gas, manual)		Lithium	
1.4	Type of operation (hand, pedestrian, standing, seated, order picker)		Seated forklift	
1.5	Load capacity / rated load	Q (lb)	5,000	6,000
1.6	Load center distance	C (in)	24	
1.8	Load distance, center of drive axle to fork	x (in)	18.3	18.9
1.9	Wheel base	y (in)	65	69
Weights				
2.1	Service weight including engine	lb	8,250	9,460
2.2	Axle loading, laden front / rear	lb	12,100 / 1,650	14,340 / 1,720
2.3	Axle loading, unladen front / rear	lb	3,080 / 5,170	3,630 / 5,830
Wheels, Chassis				
3.1	Tires (solid rubber, superelastic, pneumatic, polyurethane)		Solid pneumatic	
3.2	Tire size, front		7-12-12PR	28x9-15-14PR
3.3	Tire size, rear		6-9-10PR	6.50-10-10PR
3.5	Wheels, number front / rear (x = driven wheels)		2x / 2	
3.6	Track width, front	b10 (in)	38	39
3.7	Track width, rear	b11 (in)	39	
Basic Dimensions				
4.1	Mast / fork carriage tilt forward / backward	a/b (°)	6 / 12	
4.2	Lowered mast height	h1 (in)	79	81
4.3	Free lift	h2 (in)	5.5	5.9
4.4	Lift height	h3 (in)	118	
4.5	Extended mast height	h4 (in)	158	162
4.7	Overhead load guard (cab) height	h6 (in)	84	85
4.8	Seat height / standing height	h7 (in)	41	
4.12	Coupling height	h10 (in)	16	17
4.19	Overall length	l1 (in)	151	157
4.20	Length to face of forks	l2 (in)	103	109
4.21	Overall width	b1 (in)	45 / 46	47 / 48
4.22	Fork Dimensions	s/e/l (in)	1.6 / 4.7 / 48	1.8 / 4.8 / 48
4.24	Fork carriage width	b3 (in)	41	43
4.31	Ground clearance, under mast, laden	m1 (in)	4.7	5.5
4.32	Ground clearance, center of wheelbase	m2 (in)	6.7	7.5
4.33	Right angle stack with 40x48 pallet	Ast (in)	146.1	155.1
4.34	Right angle stack with 32x48 pallet	Ast (in)	154.1	162.1
4.35	Turning radius	Wa (in)	89	96
Performance Data				
5.1	Travel speed, laden / unladen	mph	11.2 / 11.8	11.8 / 11.8
5.2	Lift speed, laden / unladen	fpm	98 / 114	102 / 110
5.3	Lowering speed, laden / unladen	fpm	79 / 83	75 / 81
5.5	Max. Drawbar pull, laden / unladen	lbf	3,372 / 2,697	4,720 / 3,372
5.7	Max. Gradient performance, laden / unladen	%	20 / 20	
5.10	Service brake		Hydraulic	
E-Motor				
6.1	Battery voltage, nominal capacity K5	V/Ah	76.8/150	76.8/205
6.2	Battery weight	lb	240	290
6.7	Battery charger	V	Built-in single phase 110	
7.1	Drive motor rating S2 60 min	HP	20	27
7.2	Lift motor rating S3 15 min	HP	32	38
7.3	Drive motor control mode		MOSFET/PMSM	
7.4	Lifting motor control mode		MOSFET/PMSM	
7.5	Controller type		ACM80R350-CE	SZ8744-DDNLZN-ZC02-UL
Other				
10.1	Operating pressure for attachments	psi	2,683	
10.2	Oil volume for attachments	in3/min	3,050	
10.4	Hydraulic oil capacity	in3	3,660	4,270
10.7	Sound level at driver's ear according to EN 12 053	dB	72	73

NOBLELIFT reserves the right to make technical changes and improvements to our products to maintain or enhance the quality, delivery, and efficiency.



Kubota Engine

56.2 HP/2,600 rpm

High Power Engine - Kubota WG Series

High performance, durability and excellent fuel efficiency.

Type: Inline 4

Model: WG2503-L-E3

Number of cylinders: 4

Bore x Stroke: 88mm x 102.4mm

Displacement: 2.491L / 152cu in


Rated output: 41.3(55.4hp)/2600kw/rpm

Rated torque: 178 Nm @ 2000 rpm

Powerful high-output engine provides excellent acceleration, gradeability and fast travel speed.



ENVIRONMENTALLY FRIENDLY







KUBOTA LPG engines meet the EPA Tier 2 / CARB Tier 3 and EU Stage V emission regulations for engine exhaust emissions.

NOBLELIFT has used environment friendly materials when possible — Including non-asbestos brake shoes and a new type of sealing gasket. We are committed to pursuing a clean environment.



Mast Table ALPHA 50-60 LPG												
Designation	Lift height h3 (in)		Free lift h2 (in)		Closed mast height h1 (in)		Extended mast height h4 (in)		Tilt forward / backward a/b (°)		Capacity table (lb) C=24in without attachment	
	ALPHA 50 LPG	ALPHA 60 LPG	ALPHA 50 LPG	ALPHA 60 LPG	ALPHA 50 LPG	ALPHA 60 LPG	ALPHA 50 LPG	ALPHA 60 LPG	ALPHA 50 LPG	ALPHA 60 LPG	ALPHA 50 LPG	ALPHA 60 LPG
Two-stage ZT	79	79	5.5	5.7	64	61	120	122	6 / 12	6 / 12	5,000	6,000
	98	98	5.5	5.7	69	71	140	142	6 / 12	6 / 12	5,000	6,000
	106	106	5.5	5.7	73	75	147	150	6 / 12	6 / 12	5,000	6,000
	118	118	5.5	5.7	79	81	159	162	6 / 12	6 / 12	5,000	6,000
	130	130	5.5	5.7	84	87	171	173	6 / 12	6 / 12	5,000	6,000
	138	138	5.5	5.7	88	91	179	181	6 / 12	6 / 12	5,000	6,000
	142	142	5.5	5.7	92	95	183	185	6 / 12	6 / 12	5,000	6,000
	146	146	5.5	5.7	94	97	187	189	6 / 12	6 / 12	5,000	6,000
	150	150	5.5	5.7	96	99	191	193	6 / 12	6 / 12	5,000	6,000
	157	157	5.5	5.7	102	105	199	201	6 / 12	6 / 12	5,000	6,000
	169	169	5.5	5.7	108	110	210	213	6 / 6	6 / 6	4,620	6,000
	177	177	5.5	5.7	112	114	218	221	6 / 6	6 / 6	4,400	6,000
	189	189	5.5	5.7	118	120	230	232	6 / 6	6 / 6	3,960	5,940
	197	197	5.5	5.7	122	124	238	240	6 / 6	6 / 6	3,740	5,610
	217	217	5.5	5.7	132	134	258	260	3 / 6	3 / 6	3,300	4,950
	236	236	5.5	5.7	142	144	277	280	3 / 6	3 / 6	2,530	3,410
Two-stage FFL	98	98	30	33	71	78	140	143	6 / 12	6 / 12	5,000	6,000
	106	106	34	37	75	82	147	150	6 / 12	6 / 12	5,000	6,000
	118	118	38	41	79	86	159	162	6 / 12	6 / 12	5,000	6,000
	130	130	44	49	85	94	171	174	6 / 12	6 / 12	5,000	6,000
	142	142	50	55	91	100	183	186	6 / 12	6 / 12	5,000	6,000
Three-stage FFL	157	157	59	63	101	108	199	202	6 / 12	6 / 12	5,000	6,000
	157	157	36	38	77	83	199	202	6 / 6	6 / 6	4,840	5,940
	169	169	40	42	81	82	211	213	6 / 6	6 / 6	4,620	5,720
	177	177	43	44	84	86	221	223	6 / 6	6 / 6	4,290	5,280
	189	189	46	48	88	94	231	233	6 / 6	6 / 6	4,070	5,060
	197	197	49	51	90	96	238	241	6 / 6	6 / 6	3,740	4,730
	217	217	56	57	97	103	258	261	3 / 6	3 / 6	2,860	3,630
	236	236	64	64	105	109	278	280	3 / 6	3 / 6	1,870	2,640



Identification				
1.1	Manufacturer		NOBLELIFT	
1.2	Model		ALPHA 50 LPG	ALPHA 60 LPG
1.3	Drive (electric – battery or mains, diesel, petrol, gas, manual)		LPG	
1.4	Type of operation (hand, pedestrian, standing, seated, order picker)		Seated forklift	
1.5	Load capacity / rated load	Q (lb)	5,000	6,000
1.6	Load center distance	C (in)	24	
1.8	Load distance, center of drive axle to fork	x (in)	18.3	18.5
1.9	Wheel base	y (in)	65.4	69.3
Weights				
2.1	Service weight including engine	lb	8,370	9,360
2.2	Axle loading, laden front / rear	lb	11,761 / 1,609	13,596 / 1,764
2.3	Axle loading, unladen front / rear	lb	3,520 / 4,850	3,850 / 5,510
Wheels, Chassis				
3.1	Tires (solid rubber, superelastic, pneumatic, polyurethane)		Solid pneumatic	
3.2	Tire size, front		7-12-12PR	28x9-15-14PR
3.3	Tire size, rear		6-9-10PR	6.50-10-10PR
3.5	Wheels, number front / rear (x = driven wheels)		2x / 2	
3.6	Track width, front	b10 (in)	38.3	39.4
3.7	Track width, rear	b11 (in)	38.6	
Basic Dimensions				
4.1	Mast / fork carriage tilt forward / backward	a/b (°)	6 / 12	
4.2	Lowered mast height	h1 (in)	78.5	80.9
4.3	Free lift	h2 (in)	5.5	5.7
4.4	Lift height	h3 (in)	118.1	
4.5	Extended mast height	h4 (in)	158.5	161.6
4.7	Overhead load guard (cab) height	h6 (in)	83.9	84.6
4.8	Seat height / standing height	h7 (in)	40.6	41.3
4.12	Coupling height	h10 (in)	15.7	16.5
4.19	Overall length	l1 (in)	145.6	151.2
4.20	Length to face of forks	l2 (in)	103.5	109.1
4.21	Overall width	b1 (in)	45.3 / 45.8	47.1 / 48.4
4.22	Fork Dimensions	s/e/l (in)	1.6 / 4.7 / 48	1.8 / 4.8 / 48
4.24	Fork carriage width	b3 (in)	41	43.3
4.31	Ground clearance, under mast, laden	m1 (in)	4.7	5.5
4.32	Ground clearance, center of wheelbase	m2 (in)	6.7	7.5
4.33	Right angle stack with 40x48 pallet	Ast (in)	147.1	154.7
4.34	Right angle stack with 32x48 pallet	Ast (in)	155.1	163.1
4.35	Turning radius	Wa (in)	89.4	96.5
Performance Data				
5.1	Travel speed, laden / unladen	mph	11.2 / 11.2	11.8 / 12.4
5.2	Lift speed, laden / unladen	fpm	114 / 118	90 / 94
5.3	Lowering speed, laden / unladen	fpm	78.7 / 82.7	80.7 / 84.7
5.5	Max. Drawbar pull, laden / unladen	lbf	4,946 / 2,923	5,171 / 3,830
5.7	Max. Gradient performance, laden / unladen	%	25 / 20	
5.10	Service brake		Hydraulic	
Engine				
7.1	Model		Kubota WG2503-L	
7.2	Engine power rating ISO1585	HP	56.2	
7.3	Rated speed	rpm	2600	
7.4	Number of cylinders / displacement	in3	4 / 152	
7.5	Max. torque	ft-lb/rpm	126 / 1,800	
7.9	Nominal voltage	V	12	
7.10	Battery capacity	V/Ah	12/80	
Transmission				
8.1	Transmission type		Hydrodynamic	
8.2	Gear forward / backward		1 / 1	
8.3	Shifting mode		Hydraulic	
Other				
10.1	Operating pressure for attachments	psi	2,680	
10.2	Oil volume for attachments	in3/min	3,051	
10.4	Fuel tank volume	in3	3,661	4,271

NOBLELIFT reserves the right to make technical changes and improvements to our products to maintain or enhance the quality, delivery, and efficiency.

A GLOBAL LEADER

NOBLELIFT is a global leader in Lithium Technology. We manufacture more than 200 categories and around 30 series of each product. Our products are designed to meet different application demands and are well accepted by our customers in more than 100 countries and regions in Europe, America, Asia, Africa and more.

Products include: sit-down forklifts, rough terrain forklifts, narrow aisle forklifts, walkie-stackers, order pickers, electric pallet trucks, scissor lifts, tuggers, tow tractors, scrubbers/sweepers, lift tables, manual pallet jacks and more.



FORKLIFTS



NARROW AISLE



STACKERS



POWERED PALLET TRUCKS



SCISSOR LIFTS



TUGGERS



SCRUBBERS

NOBLELIFT
N O R T H A M E R I C A

2475 S. Wolf Road
Des Plaines, IL 60018
T: 847-595-7100
F: 847-595-7200
sales@nobeliftna.com
www.nobeliftna.com



Website

AUTHORIZED DEALER

