



The Egyptian Lacquer Mfg. Co.

P. O. Box 680309 • 37068-0309 113 Fort Granger Drive • 37064-2918 • Franklin, TN
(615) 790-3881 • FAX (615) 790-3831 • egyptian@egyptcoat.com

CW-1000 (Clear)

EW-1100 (Brown tinted)

EW-1200 (Gray tinted)

AGGREGATE CONCRETE CURE AND SEAL

CW-1000 / EW-1000 AGGREGATE CONCRETE CURE AND SEAL is a high gloss, UV resistant solvent based acrylic exposed aggregate sealer available in clear and brown tinted. **CW-1000 / EW-1100 / EW-1200** offers improved resistance to rain, sun, stains, freezing temperatures, and other pollutants. **CW-1000 / EW-1100 / EW-1200** superior adhesion to properly prepared concrete. **CW-1000 / EW-1100 / EW-1200** applied to exposed aggregate will also help eliminate loose pebbles and premature wear. **CW-1000 / EW-1100 / EW-1200** can be used for curing and sealing concrete.

Features:

- High solids, durable and weather resistant.
- Dustproofing most concrete surfaces.
- UV resistant and high gloss finish.

Recommended Applications:

- Driveways
- Concrete Walkways
- Masonry
- Concrete Patio
- Brick

PREPARATION: Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless the previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Concrete must be porous enough to accept water. Dense concrete surfaces may require mechanical preparation to accept a sealer. Apply only when surface and air temperatures are above 50° F and below 90° F. If applied outside those limits, the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Not that in direct sunlight, substrate temperature can exceed 150° F can cause bubbling or solvent popping.

APPLICATION: For exterior application, only. Perform test to ensure compatibility. Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can or other metal container with solvent resistant roller. Use a long nap roller for exposed aggregate, a medium nap roller for textured surfaces and a short nap roller for smooth surfaces. Keep roller soaked. Wait until the surface is tack-free before applying a second coat by cross-rolling perpendicular to the first coat. Do not thin product. Foot traffic should be avoided for 4-6 hours. Vehicle traffic should be avoided for 48 hours. Do not apply if rain is imminent. Cooler temperatures or increased humidity will slow the drying time.

Seller warrants that the products delivered hereunder are of uniform quality within manufacturing tolerances.

Any suggestions made by us covering the use of our products are based on experience and/or tests believed to be reliable. THE USE OF ANY PRODUCT OF OUR MANUFACTURE BEING COMPLETELY BEYOND OUR CONTROL HOWEVER, INCLUDING FOR EXAMPLES THE METHODS AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED (EXCEPT AS STATED ABOVE) OR IMPLIED, IS MADE. The Buyer should determine the suitability of our products under his conditions before commercial use.

NO WARRANTY OF MERCHANTABILITY IS MADE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF



The Egyptian Lacquer Mfg. Co.

P. O. Box 680309 • 37068-0309 113 Fort Granger Drive • 37064-2918 • Franklin, TN
(615) 790-3881 • FAX (615) 790-3831 • egyptian@egyptcoat.com

CLEANUP: Clean up tools with Xylene, Toluene, or Lacquer Thinner. Do not use Paint Thinner, Mineral Spirits or water.

MAINTENANCE: Clean sealed surface with water only. Reseal surface as needed, but no more often than every two years to prevent buildup of sealer.

WARNING COMBUSTIBLE. EYE, SKIN & RESPIRATORY IRRITANT: Contains Aromatic Naphtha. Do not use near heat, sparks or open flames. Avoid contact with eyes and prolonged contact with skin. Use only with adequate ventilation. Do not inhale vapors. Do not ingest. See Safety Data Sheet (SDS) for more info.

SHELF LIFE: Up to 1-year from manufacture date in its original, unopened container stored at room temperature.

TECHNICAL INFORMATION

Weight per gallon:	7.7 – 7.9 pounds	Application:	Spray or Dip
Solids:	25% wt. (±2%) 20% vol. (±2%)	Substrate:	Exposed Aggregate
Dry Time:	Tack Free – 1-2 hours Foot traffic – 4-6 hours Heavy traffic – 24-48 hours	Surface Preparation:	Clean and Dry
Application Temperature:	50° - 80° F	Storage:	Keep lid on tight Store at room temperature
Reduction:	None. Use as supplied		
Coverage:	Single coat: 100-150 sq. ft.* Double coat: 200-300 sq. ft.*		

*Rates vary depending upon surface porosity, texture, or application method.

Seller warrants that the products delivered hereunder are of uniform quality within manufacturing tolerances.

Any suggestions made by us covering the use of our products are based on experience and/or tests believed to be reliable. THE USE OF ANY PRODUCT OF OUR MANUFACTURE BEING COMPLETELY BEYOND OUR CONTROL HOWEVER, INCLUDING FOR EXAMPLES THE METHODS AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED (EXCEPT AS STATED ABOVE) OR IMPLIED, IS MADE. The Buyer should determine the suitability of our products under his conditions before commercial use.

NO WARRANTY OF MERCHANTABILITY IS MADE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF