

SAFETY DATA SHEET

Date Issued	4 October 2016		
Document Nbr			
Revision	0		
Date Revised	4 October 2016		

Steam Glo

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards

SECTION 1 - IDENTIFICATION

1.1 TRADE NAME: Steam Glo

SYNONYMS: N/A CAS#: Mixture

1.2 PRODUCT USE: Cleaning Product

1.3 SUPPLIER/MANUFACTURER'S NAME: Savin Products Company, Inc.

ADDRESS: 214 High Street, Randolph, MA 02368 USA

BUSINESS PHONE: (781) 961-2744

EMAIL: info@savinproducts.com
WEB SITE INFORMATION: www.savinproducts.com

1.4 EMERGENCY PHONE NUMBERS: 1 (800) 424-9300 (CHEMTREC U.S. - 24 HRS.)

SECTION 2 - HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a clear, thin, liquid with a mild odor.

Health Hazards: This product may cause severe skin burns and eye damage. Repeated exposure may cause skin irritation. Vapors or mist may

cause respiratory tract irritation. May be harmful if swallowed.

Flammability Hazards: This product is non-flammable. **Reactivity Hazards:** This product is reactive to metals.

Environmental Hazards: The environmental effects of this product have not been fully investigated.

Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression

equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS CANADA (WHMIS) SYMBOLS GHS Hazard Symbols



Complies with WHMIS 2015





Signal Word: DANGER!

2.1 GHS LABELING AND HAZARD CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by the OSHA and described in 29 CFR 1910.1200(d). Component(s) Contributing to Classification(s):

component(s) contributing to classification(s).

All ingredients

2.2 LABEL ELEMENTS

GHS Hazard Classification(s):

Skin Corrosion/Irritation - Category 1C Eye Damage/Irritation - Category 1 Corrosive to Metals - Category 1 Acute Toxicity-Oral - Category 4

Page 1 of 7 Printed: 4. Oct. 2016

Precautionary Statement(s): Hazard Statement(s):

Causes severe skin burns and eye

damage

Wear protective gloves/protective clothing/eye

Causes serious eye damage protection/face protection.

May be corrosive to metals Avoid exposure

Harmful if swallowed Use only outdoors or in a well-ventilated area

Keep only in original container.

Wash hands thoroughly after handling

Response Statement(s):

IF SWALLOWED: Call a Poison Control Center/Doctor. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Call a Poison Center/Doctor if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage Statement(s):

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Statement(s):

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 HEALTH HAZARDS OR RISKS FROM EXPOSURE:

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The most significant routes of overexposure for this product are by contact with skin or eyes, and inhalation of mists or spray. The symptoms of overexposure are described in the following paragraphs.

ACUTE:

INHALATION: Inhalation of mist from this product may causes respiratory irritation. May cause dizziness, nausea and/or breathing difficulties.

SKIN CONTACT: Exposure to this product may cause skin irritation.

EYE CONTACT: Contact with eyes can cause serious irritation with redness, tearing, and blurred vision.

INGESTION: Ingestion can cause gastric distress and nausea. Can result in damage to mouth, throat, esophagus and stomach.

CHRONIC: The effects of long term, low level exposures to this product have not been determined.

TARGET ORGANS: ACUTE: Eyes, Skin CHRONIC: No data available for this product.

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

COMPOSITION	WT. PERCENTAGE	CAS#	HAZARD CLASSIFICATION		
Water	85-95	7732-18-5	None		
Potassium Hydroxide	1-5	1310-58-3	Corrosive to Metals - Cat 1, Acute Toxicity, Oral - Cat 4, Skin Corrosion/Irritation - Cat 1A, Eye Damage/Irritation – Cat 1, Acute Aquatic Toxicity - Cat 3		
Tetrasodium Ethylenediamine- tetraacetate	1-5	64-02-8	Corrosive to Metals - Cat 1, Acute Inhalation Toxicity - Cat 4, Skin Corrosion/Irritation Cat 2, Eye Damage/Irritation – Cat 1, STOT RE Inhalation - Cat 2		
Balance of other ingredients are less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers)					

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format.

SECTION 4 - FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Contact with eyes may cause severe irritation with redness and tearing with possible tissue damage. Prolonged skin exposure may cause moderate to severe skin irritation.

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

Water Spray: YesCarbon Dioxide: YesFoam: YesDry Chemical: YesHalon: YesOther: Any "C" Class

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

Combustion may produce noxious and irritating gases. Explosion Sensitivity to Mechanical Impact: No Explosion Sensitivity to Static Discharge: No

FLASH POINT: >200°F (>93°C)

AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %): Lower: NA, Upper: NA


5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM



Hazard Scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:

See Section 8.2 for Exposure Controls.

6.2 ENVIRONMENTAL PRECAUTIONS:

Keep spilled material out of all sewers and open bodies of water.

6.3 SPILL AND LEAK RESPONSE:

Contain spill if safe to do so. Cover or absorb spilled liquid with sand, earth, or other inert material. Clean up spill immediately and place in appropriate containers. Keep spill out of sewers and open bodies of water. **CAUTION:** Floor may become slippery.

Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13 Disposal Considerations).

SECTION 7 – HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

As with all chemicals, avoid getting this product **ON YOU** or **IN YOU**. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

7.2 STORAGE AND HANDLING PRACTICES:

Containers of this product must be properly labeled. Store containers in a cool, dry location. Keep container tightly closed when not in use. Keep away from strong alkalis, bases, and reactive materials.

7.3 SPECIFIC USES:

Developed specifically for carpet cleaning and extraction .

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

CHEMICAL NAME	CAS#	ACGIH TLV	OSHA TWA
Water	7732-18-5	Not Listed	Not Listed
Potassium Hydroxide	1310-58-3	2 mg/m3	Not Listed
Tetrasodium Ethylenediamine- tetraacetate	64-02-8	Not Listed	Not Listed

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada.

RESPIRATORY PROTECTION: Not required when using this product. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

EYE PROTECTION: Safety glasses or goggles are recommended. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Standards of Canada.

HAND PROTECTION: Chemical resistant gloves are recommended to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standard of Canada.

BODY PROTECTION: Not normally required when using this protect. If necessary, refer to U.S. OSHA 29 CFR 1910.132 (also OSHA Technical Manual). or appropriate Standard of Canada.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE (PHYSICAL STATE) AND COLOR: Clear, thin, colorless VAPOR PRESSURE (mm Hg @ 68°F (20°C)): Not available.

liquid with a mild odor.

ODOR: Mild. ODOR THRESHOLD: Not available.

pH: 13.7

MELTING/FREEZING POINT: Not available.

BOILING POINT: 212°F

FLASH POINT: >200°F (>93.3°C)

EVAPORATION RATE (n-BuAc=1): Not available. FLAMMABILITY (SOLID, GAS): Not applicable.

UPPER/LOWER FLAMMABILITY OR EXPLOSION LIMITS: Not available.

PARTITION COEFFICIENT (n-octanol/water): Not applicable.

AUTO-IGNITION TEMPERATURE: Not applicable. **DECOMPOSITION TEMPERARE:** Not available.

VISCOSITY: Not available.

VAPOR DENSITY: Not available.

RELATIVE DENSITY: Not available.

SPECIFIC GRAVITY: 1.05 @ 25°C

SOLUBILITY IN WATER: Complete soluble.

WEIGHT PER GALLON: 8.8 Lb/gal @ 20°C

9.2 OTHER INFORMATION:

No additional information available.

SECTION 10 – STABILITY AND REACTIVITY

10.1 REACTIVITY:

Not reactive

10.2 STABILITY:

Stable under conditions of normal storage and use.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

None known

10.4 CONDITIONS TO AVOID:

Incompatible materials.

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Aluminum

10.6 HAZARDOUS DECOMPOSITIONS PRODUCTS:

Strong solutions react with aluminum, zinc, and tin to form hydrogen gas.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

Toxicity data is available for the following products - None

SUSPECTED CANCER AGENT: The following ingredients are found on one or more of the following lists: FEDERAL OSHA Z LIST, NTP,

CAL/OSHA, IARC and therefore are considered to be, or suspected to be, a cancer-causing agent by these agencies.

IRRITANCY OF THE PRODUCT: Contact with this product can be irritating to exposed skin and eyes.

SENSITIZATION TO THE PRODUCT: This product is not considered a skin and respiratory sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No information available

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: Not classified as a specific target organ toxicity - single exposure.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: Not classified as a specific target organ toxicity - repeated exposure.

CHRONIC EFFECTS: The effects of long term, low level exposures to this product have not been determined.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 TOXICITY:

Toxic to aquatic life. Do not discharge to streams, ponds, or waterways.

12.2 PERSISTENCE AND DEGRADABILITY:

No specific data available for this mixture.

12.3 BIOACCUMULATIVE POTENTIAL:

No specific data available for this mixture.

12.4 MOBILITY IN SOIL:

No specific data available for this mixture.

12.5 OTHER ADVERSE EFFECTS:

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

This product, if disposed of as shipped, is not considered a hazardous waste as specified in 40 CFR 261.

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, and those of Canada.

SECTION 14 – TRANSPORTATION INFORMATION

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation. NOTE: Limited quantities of corrosive material (Class 8) in Packing Group III are excepted from labeling requirements, unless the material is offered for transportation or transported by aircraft, and are excepted from the specification packaging requirements of this subchapter when packaged in combination packagings according to this paragraph. For transportation by aircraft, the package must also conform to the applicable requirements of sec. 173.27 of this part. A limited quantity package that conforms to the provisions of this section is not subject to the shipping paper requirements of subpart C of part 172 of this subchapter, unless the material meets the definition of a hazardous substance, hazardous waste, marine pollutant, or is offered for transportation and transported by aircraft or vessel, and is eligible for the exceptions provided in sec. 173.156 of this part. In addition, shipments of limited quantities are not subject to subpart F (Placarding) of part 172 of this subchapter. Each package must conform to the packaging requirements of subpart B of this part and may not exceed 30 kg (66 lb) gross weight.

14.2 UN IDENTIFICATION NUMBER: UN 1760

14.3 PROPER SHIPPING NAME: Corrosive liquids, n.o.s. (Potassium Hydroxide, Tetrasodium

Ethylenediaminetetraacetate)

14.4 HAZARD CLASS NUMBER AND DESCRIPTION: Corrosive, Class 8

14.5 PACKING GROUP: PG III

DOT LABELS REQUIRED: Corrosive



NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER: 154

14.6 ENVIRONMENTAL HAZARDS (RQ QUANTITY): Not applicable.

MARINE POLLUTANT: The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

14.7 SPECIAL PRECAUTION FOR USER:

Use caution and avoid exposure.

14.8 INTERNATIONAL TRANSPORTATION:

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is considered as dangerous goods.

Note: Packaging does not comply with IATA regulations and cannot be shipped by aircraft.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is considered as dangerous goods.

SECTION 15 – REGULATORY INFORMATION

15.1 SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

See below

15.2 UNITED STATES REGULATIONS:

SARA REPORTING REQUIREMENTS: This product is not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

ACUTE HEALTH: YES CHRONIC HEALTH: NO FIRE: NO REACTIVITY: NO

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Potassium Hydroxide CAS# 1310-58-3 (1000#)

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does not contain ingredients that are on the California Proposition 65 lists.

15.3 CANADIAN REGULATIONS:

CANADIAN DSL/NDLS INVENTORY STATUS: All components are DSL listed, NDSL listed, and/or are exempt from listing.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LIST: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION AND SYMBOLS: This is considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and is therefore subject to the labeling and SDS requirements of the Workplace Hazardous Materials Information System (WHMIS) 2015.

SECTION 16 – OTHER INFORMATION

16.1 ABBREVIATIONS AND ACRONYMS:

EPA: United State Environmental Protection Agency **IMDG:** International Maritime Code for Dangerous Goods

DOT: US Department of Transportation **IATA:** International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

DATE OF CURRENT REVISION: October 4, 2016 DATE OF LAST REVISION: October 4, 2016

Disclaimer: To the best of Savin Products Company Inc. knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability, or completeness is not guaranteed and no warranties of any type either express or implied are provided. The information contained herein relates only to this specific product.