

RS8-44 GEN·4

CONSTRUCTION TELEHANDLERS



KEY FEATURES

- ✓ Simple F-N-R joystick operation
- ✓ Load material at 40' without moving the machine
- ✓ Capacity for standard construction materials
- ✓ 360° operator visibility

KEY SPECIFICATIONS

- ✓ 8,000 lbs. (3629 kg) maximum lifting capacity
- ✓ 44' 0" (13.4 m) maximum lifting height
- ✓ 7,000 lbs. (3176 kg) lift capacity to 44' 0" (13.4 m)
- ✓ 120 hp (89 kW) Deutz diesel engine

IMPERIAL

CAPACITIES	Max. capacity	8000 lb
	Max. lifting height	44 ft
	Maximum outreach	30 ft 5 in
WEIGHT AND DIMENSIONS	Length to face of forks	19 ft 1 in
	Overall width	8 ft 2 in
	Overall height	7 ft 10 in
	Wheelbase	10 ft
	Ground clearance	16 in
	Tilt-up angle	12 °
	Tilt-down angle	112 °
	External turning radius	13 ft 8 in
	Unladen weight (with forks)	23500 lb
	Overall weight	23501 lb
ENGINE	Standard tires	13 x 24
	Frame leveling longitudinal +/-	10 °
	Frame leveling corrector	10 °
	Engine brand	Deutz
TRANSMISSION	Engine nom	Tier 4 final
	Engine model	TCD 3.6 L4
	Engine power (Hp/kW)	120 Hp / 89 kW
	Max. torque / Engine rotation	354 ft/lbs @ 1600 rpm
HYDRAULICS	Transmission type	Torque converter with powershift gearbox
	Number of gears (forward / reverse)	3 / 3
	Travel speed (laden)	20 mph
	Max. travel speed	20 mph
	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
TANK CAPACITIES	Axle Manufacturer	Dana
	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	41 US gpm-3002 PSI
MISCELLANEOUS	Hydraulic oil	31 US gal
	Diesel Exhaust fluid (AdBlue® type)	5 US gal
	Fuel	47 US gal
MISCELLANEOUS	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Cab certification	ROPS/FOPS
	Controls	Single Joystick FNR

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.




STANDARD FEATURES

- Boom Tip Lift Hook
- Rear Axle Stabilization
- Crab mode
- Engine Block Heater
- Back-Up Alarm
- 12 Volt Battery
- Self-Leveling Forks
- Four Wheel Drive
- Multi-Function Display Screen
- Wet disc brakes
- 12 Volt Power Port
- 3 speeds

OPTIONAL FEATURES

- Easy Manager
- Solid Rubber Tires
- Enclosed Cab with Heat and A/C
- Rock Tread - Air Foam Tires
- Enclosed Cab with Heat and Defrost
- PWP System 3-Section Boom
- Front Outriggers
- Light Package - LED
- Foam Filled Tires
- Suspension Seat
- Rearview Camera



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT