

## Portable Compressors

# MOBILAIR® M58 Utility



### Versatile

The MOBILAIR® M58 Utility rotary screw compressor is designed for cross mounting on service vehicles. It delivers 210 cfm at 100 psig and is ideal for public works, utility, and other field work vehicles.

### User-friendly

The M58 Utility is very compact. It has both long and short side forklift slots as well as a single-point lifting bail for easy mounting/dismounting. The eye-level, curb side instrument panel features an easy to operate SIGMA CONTROL® SMART electronic controller with protective metal cover. Another important feature is the large 28 gallon fuel tank that provides extended operation - up to 10 full hours!

### Efficient and Reliable

A heavy-duty 4-cylinder engine direct coupled to our energy saving SIGMA PROFILE® airend produces more air with less horsepower. A high capacity cold start battery ensures reliable operation even under extreme conditions.

The M58 Utility's rugged steel cabinet is powder-coated and built to take the harshest conditions while protecting the machine from dirt, water, and other contaminants.

The engine and compressor have separate inlet filters with maintenance indicators. This protection, combined with a high efficiency cooling system, allows the unit to operate in ambient temperatures up to 122°F.

### Standard Features:

- SIGMA PROFILE rotary screw airend produces more air with less horsepower
- Heavy-duty 4-cylinder Kubota diesel engine meets Tier 4 Final EPA emissions standards
- SIGMA CONTROL SMART electronic controller
- Exclusive anti-frost valve maintains optimum operating temperature and prevents tool freeze up
- Large fuel tank for up to 10 hours of continuous operation
- Powder-coated steel cabinet
- High capacity cold start battery ensures reliable operation

### Optional Features:

- Aftercooler package
- Pressures up to 145 psig

### Optional 5 year warranty

*To protect your investment, all of our MOBILAIR compressors are available with an optional 5 year warranty on the compressor airend.*

# Technical Specifications

COMPRESSOR		DIESEL ENGINE			PACKAGE		DIMENSIONS		
Model	Free Air Delivery (cfm)	Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L x W x H (in.)
M58 Utility	210 100 psig 145 psig	Kubota V2403-CR-E4B Tier 4 Final	48	2450 - 2600	1800	28	2043	2 x 3/4" 1 x 1"	84 <sup>5</sup> / <sub>8</sub> x 33 <sup>1</sup> / <sub>8</sub> x 55

Sound level maximum is 76 db(A) at 23 feet

Specifications subject to change without notice.

## Outstanding Advantages

- ✓ Removable side panels and swing open end door
- ✓ Easy to operate SIGMA CONTROL SMART electronic controller
- ✓ Two 3/4" Chicago style fittings and one 1" NPT connection ports
- ✓ Short and long side fork slots for easy mounting
- ✓ Tier 4 Final Kubota diesel engine
- ✓ Energy saving SIGMA PROFILE airend
- ✓ Extra large capacity fuel tank provides up to 10 full hours of operation
- ✓ Separate 4 micron air inlet filters protect compressor and engine
- ✓ Top exhaust port with rain cap
- ✓ Optional aftercooler package



*Built for a lifetime.*



**Kaeser Compressors, Inc.**  
511 Sigma Drive  
Fredericksburg, VA 22408 USA  
Telephone: 540-898-5500  
Toll Free: 800-777-7873  
info.usa@kaeser.com

**Kaeser Compressors Canada Inc.**  
3760 La Vérendrye Street  
Boisbriand, QC J7H 1R5 CANADA  
Telephone: (450) 971-1414  
Toll free: (800) 477-1416  
info.canada@kaeser.com

**Kaeser Compresores de México S de RL de CV**  
Calle 2 #123  
Parque Industrial Juríca  
76100 Querétaro, Qro.  
Telephone: 01 (442) 218 64 48  
sales.mexico@kaeser.com

**Kaeser Compresores de Guatemala y Cia. Ltda.**  
3a calle 6-51, zona 13  
Colonia Pamplona  
01013—Guatemala City  
Telephone: +502 2412-6000  
info.guatemala@kaeser.com