



# SUPERIOR HANG STRENGTH = REMARKABLE PERFORMANCE

The superior hang strength of WATCHDOG H3 delivers a consistent thickness for maximum waterproofing performance when it cures to 40 mils. Other waterproofing products slide down the wall and pool at the footer, leaving basement walls vulnerable to leaks and seepage. WATCHDOG WATERPROOFING® is performance-engineered to hang in place on the wall, eliminating product waste and providing exceptional waterproofing protection.

## WATCHDOG H3 WATERPROOFING:

- holds back up to 3 feet of water under hydrostatic pressure
- is specifically formulated to span concrete settling cracks, sealing against water leaks
- offers a 10 year performance warranty\*
- stays where it's sprayed for maximum protection

**YOUR LOCAL BARRIER SOLUTIONS CONTRACTOR:**

### Membrane Properties

<b>Resistance to Hydrostatic Head</b>	<b>Results:</b> 3' of water	<b>Method:</b> ASTM D-5385
<b>Type</b>	Polymer-enhanced asphalt liquid-applied membrane	
<b>Color</b>	Black	
<b>Solids</b>	64% ± 3% [percent by weight]	
<b>Density</b>	8.2 ± .15 lbs/gal	
<b>Application</b>	Airless spray	
<b>Application Temperature</b>	Minimum 20°F <sup>1</sup>	
<b>Application Thickness</b>	60 mils (wet) <sup>2</sup>	
<b>Typical Cure Time</b>	16-24 hrs [under normal conditions]	
<b>Adhesion to Concrete</b>	<b>Results:</b> Exceeds	<b>Method:</b> ASTM C-836
<b>Elongation</b>	<b>Results:</b> >1700%	<b>Method:</b> ASTM D-412
<b>Crack Bridging Ability</b>	<b>Results:</b> Passes	<b>Method:</b> ICC-ES AC29, Sec 3.1
<b>Water Vapor Permeance</b>	<b>Results:</b> <1 perm for 40-mil dry coating [grains/sf/hr]	<b>Method:</b> ASTM E-96 Wet Method
<b>Resistance to Degradation in Soil</b>	<b>Results:</b> Good	<b>Method:</b> ASTM E-154
<b>Mold Growth and Bacterial Attack</b>	<b>Results:</b> No degradation	<b>Method:</b> ASTM D-3273, ASTM D-3274

<sup>1</sup> May be applied at lower temperature by following procedure for Cold Weather Application in Application Instructions.  
<sup>2</sup> Measured in-place with ASTM D-4414 notch film gauge, wetting the 60 mil tab. Membrane cures [dries] to 40 mils.

**TREMCO** 800.876.5624  
 Barrier Solutions. TREMCOBARRIERSOLUTIONS.COM