SAFETY-VAC



SAFETY-VAC® Model 35LRP500-DOT-T

Power System

- Lombardini Model 15LD electric start 10 hp air-cooled diesel engine
- No spill oil drain
- Full spark arrest
- Dual V-belt drive
- Nash Liquid ring vacuum pump system
- Vacuum 24 HG @ 200 CFM

Recovery & Containment

- One 500-gallon tank with access hatch
- Automatic system overfill protection
- 2" diameter suction and pressure ports
- 50' capacity live vacuum hose reel
- 50' of 1.5" fuel rated hose
- Recovery hose is neoprene with end-to-end electrical continuity
- 18" surface recovery tool and wand extension with replaceable neoprene squeegee blades and height adjustment for multi-surface operation
- Aluminum quick-connect hose fittings
- Reverse flow evacuation and transfer cycle allows operator to use pressure-side blower power to rapidly offload recovered material
- 50' static grounding reel
- 55 Gallon barrel with diverter valve for dissimilar material collection
- Tank drain valve

Platform

- 5' x 12' 12,000lb gross vehicle weight tandem axle trailer
- Stainless steel fasteners
- Front wheel hubs have electric brakes

Service Rating

- High speed liquid and particle recovery from ground level to 25' below grade
- Powered emptying and liquid transfer
- One year warranty from engine and blower manufacturers
- Two year warranty on material workmanship and containment