

## **Bone Stock 110 FWD Wire Compacts 2026**

If it doesn't say you can do it, don't assume that you can. There are no grey areas in these rules. These rules listed below are how you can build your car. NO EXCEPTIONS. All cars should be built to these rules. IF YOU HAVE ANY RULE QUESTIONS CALL BRANDIN AND ONLY BRANDIN 608-434-4317!! PLEASE NO CALLS AFTER 8PM.

### **GENERAL CAR PREP**

**FRESH CARS ONLY (2 vans per team) Front wheel drive only. No all wheel drive. No sub swapping. Engine must be make to make and direct bolt in.**

**NO SPRAY FOAM BEFORE INSPECTION**

1. All cars need to be stripped and cleaned out for safety. May remove metal but cannot add.
2. The battery and gas tank must be inside the car, secure them, no leaks. No stock gas tanks allowed.
3. May run stock, mud, donut or forklift tires. Bead protectors are allowed.
4. Hood and Trunk – May 9 wire (6) spots on each, sheet metal to sheet metal only. Hoods must have fire hole. May use (2) pieces of  $\frac{3}{4}$ " all thread in front mounts only. Must run through frame but keep stock mounts. May use (3)  $\frac{3}{4}$ " washers, (3) nuts and (1) 3"x3" hood plates. All thread cannot be welded to the side of the frame. This is considered (2) of the (6) allowed spots for hood hold down, NOT in addition to. Optional: 2 of these spots can go down to the bumper, front and rear. May 90 trunk. No sheet metal creasing or shaping. Slight pre-bending allowed. Don't go overboard. Speaker deck must be factory location.
5. You may 9 wire all doors closed in 2 spots OR you may weld doors shut in 2 spots with (2) 6"x3" x 1/8". These 2 straps may not be cut up. This is either or option, not both. MUST have chain, 9 wire or 3" strap in front window.
6. Cage – Needs to be a 4-point cage. Halo optional. If running halo, it must be secured in 2 spots on the roof with wire or bolts. You may have a down bar on the driver and passenger sides (For safety purposes). This CANNOT reinforce the car in any way. Door bars cannot exceed 60". Door bars and dash bars must be 4" away from firewall and wheel tub. Gas tank protector must be 6" away from all sheet metal.
7. Bumpers – May use any automobile bumper / aftermarket bumper or may use a 4x4 square tube bumper. Bumpers can be 8" tall MAX. Cannot be wider than fenders. Bumper shocks can be up to 3x3 square tube 8" long, SINGLE PASS WELD, NO GUSSETS. May shorten frame up to core support. Rear bumpers must remain in stock location.
8. Struts must be stock, but struts may be clamped or strut risers may be used.
9. Only aftermarket parts allowed: Battery box, tranny cooler, gas tank, shifter, headers, and wiring harness. No carb set ups. THERE SHOULD BE NO QUESTIONS ON RULES. WHATS ABOVE IS WHAT YOU GET!! THIS IS A VERY EASY BUILD! BONESTOCK!! DO NOT OVERTHINK IT!