CLOPAY COMMERCIAL - MODEL 3591S replacement slab solutions





SHIPLAP SECTIONS WITH RIBS

Clopay 3591S sections feature a 3-layer, polyurethane insulated shiplap design. Ideal for use as a replacement section solution for most commercial and industrial applications.



Steel skins are protected through a tough, layered coating system, including a hot-dipped galvanized layer, a protective metal oxide pretreatment and a baked-on primer and top coat.

The 3591S sections feature a common design ribbed embossment and shiplap section joint, making it a versatile replacement section solution for many commercial service applications. 3591 sections are designed with a continuous backer strip running the top and bottom of the section, allowing them to be cut any length. The backer strips can accommodate full-body center hinges or Clopay's combination center hinge.

PANEL DESIGN



Ribbed

FEATURES


MATERIALS AND CONSTRUCTION	
Panel Thickness	1-5/8" (41 mm)
Insulation	CFC and HCFC-free polyurethane
R-value	14.86*
Thermal Break	Continuous foam
Section Joint	Shiplap
Exterior Steel	28 gauge (.015" min.) (.38 mm)
Exterior Surface	Stucco embossed, ribbed
Slab Width	24'7" (7.5 m)
Slab Height	24' or 21' (7.3 m or 6.4 m)
Exterior Colors	Standard White and Brown (24" tall sections only)
Interior Color	Standard White
End Stiles	Available in both 18 gauge single end stile and 16 gauge double end stile
Limited Warranties	10-year delamination 10-year standard paint 1-year material and workmanship

^{*}Calculated door section R-value is in accordance with DASMA TDS-163.

COLOR OPTIONS



Due to the printing process, colors may vary.



Call your local DC or sales representative to order today!

DISTRIBUTED BY:











