# clopay commercial - models 904,9040 architectural series





## **ALUMINUM FULL-VIEW DOORS**

Clopay's Model 904 showcases a contemporary design with fewer lines and angles to its appearance. With equal stile spacing, rail and stile profiles are more proportional to each other. This design provides an aesthetically pleasing appearance making it ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Model 904U features Intellicore® polyurethane insulated rails and stiles.



Frame Detail



Section Joint Seal



Reinforcing Fin (where applicable)



Model 904U\* Model 904

\*Model 904U R-value 3.8 with clear insulated glass.

#### **OPTIONS**

## **PANEL OPTIONS**





Aluminum Full-View

Solid Aluminum

#### FRAME/SOLID PANEL COLOR OPTIONS



Bronze

(Anodized)\*

Standard White



Black (Anodized)\*



(Painted)

Dark Bronze

(Anodized)\*



time may apply. The use of "Bronze (Painted)" is recommended due to slight color variation that may occur during the anodizing process.

Chocolate


(Painted)

## **CUSTOM PAINT OPTIONS**

Color Blast® finish paint system or RAL Powder Coating give you thousands of color options for endless upgrades. See your Clopay Dealer for details.









#### GLASS/PANEL OPTIONS





**Gray Tinted Glass** 















Bronze Tinted

Glass





Mirrored Glass'





Obscure Glass









Black Laminate Glass\*



Clear Acrylic

Frosted Acrylic

Midnight Gray

White Acrylic



Clear Polygal™



**SPECIALTY PRODUCTS** 

Aluminum Panel (Color-matched)

\*Glass/acrylic panels may be combined with aluminum panels. Custom glass and colors available. †5/16" clear, white, gray and bronze laminate impact rated glass is available only on 904W8/904UW8.

### PERFORMANCE OPTIONS

#### **HEAVY-DUTY HARDWARE**



Double-end Hinge



3" Track



High Performance Hardware



Center Mullions



Exhaust Port

#### **OPTIONAL WARRANTY**

Extended 8-year hardware warranty includes upgraded industrial hardware. Upgraded hardware includes 3" track and rollers, 11 gauge hinges, heavy duty brackets, solid shaft and more.



## WINDCODE®



Window Style Glass

Solid Panels

Wind Load

Joint Seal

Springs

Tracks

Hardware

Warranty

Design pressures (DP) up to 52 PSF depending on configuration. Models tested 50% greater than DP.

STANDARD SPECIFICATIONS	
Max Width	24'2" (Maximum width for Model 904U is 20'2")
Max Height	20'0"
Exterior/Interior Panel Thickness	2-1/8"
Insulation	Intellicore® polyurethane (Model 904U)
U-Factor	0.73* (Model 904U with insulated low-e argon filled glass)
R-value	3.8† (Model 904U with clear insulated glass)
Air Infiltration Rate	0.15cfm/ft <sup>2</sup>
End Stile Thickness	4.5" wide single up to 14'2" 6.5" wide double over 14'2"
Emboss	Recessed panel with smooth surface
Panel Style	Full-view or solid aluminum panel
Section Construction	6063-T5 extruded aluminum alloy



MADE IN USA

For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.











DSB glass, tempered glass, acrylic, thicknesses of 1/8", 1/4" and 1/2"

Insulated and non-insulated aluminum panels

Galvanized aircraft cable with minimum 7:1 safety factor

Impact rated (W6 and W8 only)

2" angle mount track with standard lift

TPE astragal in corrosion-resistant retainer

Inside slide lock for increased security

Material and workmanship - 1 Year

10,000 cycle springs

3" track where applicable

Steel step plate and lift handle

Standard paint - 5 Years

†Calculated door section R-value is in accordance with DASMA TDS-163.

\*Tested door U-Factor is in accordance with DASMA 105.

Commercial 10-ball steel rollers

14 gauge hinges

Hardware - 1 Year

Color Blast® finish - 5 Years