

ISX 2200

Take productivity and comfort up a notch. The ISX 2200 boasts our most advanced suspension technology – ForeFront Suspension, ensuring operator comfort. The new iCD+ Cutting System delivers unrivaled cut quality and the heavy-duty Hydro-Gear ZT-4400™ transaxle drive system provides power and durability to get the job done.

MODEL	ENGINE OPTIONS	DECK
5902089	Kawasaki® FX801V (25.5** hp/852 cc)	52" iCD
5902090	Kawasaki® FT730V-EFI (26** hp/726 cc)	52" iCD
5902088	Vanguard® 810cc EFI with Oil Guard™ (28* hp/810 cc)	52" iCD
5902079	Kawasaki® FX801V (25.5** hp/852 cc)	60" iCD+
5902080	Kawasaki® FT730V-EFI (26** hp/726 cc)	60" iCD+
5902078	Vanguard® 810cc EFI with Oil Guard™ (28* hp/810 cc)	60" iCD+

Available accessories:

Collection systems, mulch kit, trailer hitch kit, flat-free caster tires, LED light kit, service jack, professional striping kit, Kenda Terra Trac drive tires (60"), laser-edge blade sets, fender kit, Kenda Turfsteel NPT



▶ FOREFRONT SUSPENSION SYSTEM

The patented system utilizes large shocks with four upper and lower control rods that ensure the front caster bearing remains vertical through the full range of travel for an exceptionally smooth ride

▶ PREMIUM SUSPENSION SEAT

Select models feature the premium high-back suspension seat with armrests, adjustable lumbar and back recline

NEW USB Port

12V-60V, USB Type A & C located on the dash panel for easy access and charging

NEW iCD+ Cutting System

Redesigned to deliver next-level performance, increased durability and superior results

Hydro-Gear ZT-4400 transaxles

Dual-commercial transaxles with 8.3" cooling fans to repel debris

Cast-iron spindles

8" diameter with greaseable bearings for improved durability in demanding conditions

Unleaded gas capacity of 11 gallons

Rugged twin 5.5 gal fuel tank for increased productivity

24" turf-friendly rear tires

Tapered bumper with built-in tie down points

Provides added engine protection and angled design provides more ground clearance

Product shown with optional accessories and may vary.

* Power levels are stated gross horsepower at 3600 rpm per SAE J1940 as rated by Briggs & Stratton.

** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.