

ISX 800

The ISX 800 is engineered to increase efficiency and comfort. Combining next-generation Ferris technology, ForeFront Suspension with the iCD+ Cutting System, means a smoother ride and improved cut.

MODEL	ENGINE OPTIONS	DECK
5902083	Kawasaki® FT730V (24 hp**/726 cc)	52" iCD
5902084	Briggs & Stratton® CXi Series (27 hp*/810 cc)	52" iCD
5902073	Kawasaki® FT730V (24 hp**/726 cc)	60" iCD+
5902074	Kawasaki® FT730V-EFI (26 hp**/726 cc)	60" iCD+
5902075	Briggs & Stratton® CXi Series (27 hp*/810 cc)	60" iCD+
5902172	Briggs & Stratton® CXi Series EFI-ETC w/ Oil Xtend™ (27 hp*/810 cc)	60" iCD+

Available accessories:

Collection systems, mulch kit, trailer hitch kit, flat-free caster tires, LED light kit, service jack, professional striping kit, Kenda Terra Trac drive tires, laser-edge blade sets, fender kit



▶ FOREFRONT SUSPENSION SYSTEM

The patented system utilizes medium shocks with four upper and lower control rods that ensure the front caster bearing remains vertical through the full range of travel for an exceptionally smooth ride

▶ EFI-ETC ENGINE TECHNOLOGY & OIL XTEND

Select models feature the Briggs & Stratton CXi Series engine with EFI-ETC technology for easy starting and smooth performance and Oil Xtend to boost productivity and minimize downtime by 250 hours - 2.5 times longer than the industry standard

NEW USB Port

12V-60V, USB Type A & C located on the dash panel for easy access and charging

NEW iCD+ Cutting System

Redesigned to deliver next-level performance, increased durability and superior results

Integrated transmission

Commercial Hydro-Gear ZT-3400® transaxles, with 7" cooling fans, are designed for high performance and are fully serviceable

Ground speeds up to 10 mph

Cover more grass in less time for increased productivity

Cast-aluminum spindles

Greaseable bearings provide a longer usable life

23" turf-friendly rear tires

Fuel capacity of 5.5 gallons of unleaded gasoline

Product shown with optional accessories and may vary.

* Power levels are stated gross horsepower at 3600 rpm per SAE J1940 as rated by Briggs & Stratton.

** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.