

SRS Z1

Ideal for tight gates and smaller trailers the SRS Z1 offers excellent productivity in a compact frame. True to the Soft Ride Stand-on (SRS) series, the adjustable operator platform on the Z1 features suspension technology, improving operator comfort and performance.



MODEL	ENGINE OPTIONS	DECK
5901939	Kawasaki® FX600V (19 hp**/603 cc)	36"
5901941	Vanguard® (23 hp*/627 cc)	36"
5901940	Kawasaki® FX691V (22 hp**/726 cc)	48" iCD
5901942	Vanguard® (23 hp*/627 cc)	48" iCD

Available accessories:

Mulch kit, metal grass catcher, LED light kit, service jack, professional striping kit (48"), Kenda Terra Trac drive tires (48"), laser-edge blade sets (48")

SUSPENSION PLATFORM SYSTEM

The operator platform is suspended by a coil-over shock with five adjustable positions, optimizing operator comfort and increasing productivity

SPEED CONTROL SETTING

The easy locking 3-position speed control setting is conveniently located and requires no tools to facilitate smooth operation in a wide range of conditions

Fabricated 10-gauge steel deck

Double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge

Hydro-Gear ZT-3400 transaxles

Dual-commercial transaxles with 7" cooling fans with a 3-year limited warranty†

Cast-aluminum spindles

Greaseable bearings provide a longer usable life

23" turf-friendly rear tires

Commercial-grade performance optimizes stability and traction

Ground speeds up to 8 mph

Cover more grass in less time for increased productivity

6 gallon fuel capacity

Fuel tank is centrally located for improved stability and ease of fill-ups

* Power levels are stated gross horsepower at 3600 rpm per SAE J1940 as rated by Briggs & Stratton.

** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

† See operator's manual or ferrismowers.com for complete warranty details. Refer to the engine operator's manual for engine warranty details.