

SRS Z3X

Built to deliver superior traction and performance, the SRS Z3X raises the bar for stand-on productivity. With 52", 60" and 72" deck options and a pivoting front axle for extra grip on steep inclines, the Z3X increases efficiency without sacrificing safety or the trusted Ferris cut quality on even the most difficult properties.



| MODEL | ENGINE OPTIONS | DECK |
|---------|--|----------|
| 5901955 | Kawasaki® FX850V (27 hp**/852 cc) | 52" iCD |
| 5902131 | Vanguard® BIG BLOCK™ EFI-ETC with Oil Guard™ (37 hp*/993 cc) | 52" iCD |
| 5902071 | Vanguard® BIG BLOCK™ EFI-ETC with Oil Guard™ (37 hp*/993 cc) | 60" iCD+ |
| 5902170 | Vanguard® BIG BLOCK™ EFI-ETC with Oil Guard™ (37 hp*/993 cc) | 72" iCD+ |

Available accessories:

Mulch kit, metal grass catcher (52"), LED light kit, professional striping kit, Kenda Terra Trac drive tires (60" & 72"), laser-edge blade sets, Kenda Turfsteel NPT (60" & 72")

▶ 500 HOUR OIL CHANGE

Vanguard engines with Oil Guard System reduce maintenance time and costs by up to 60%[‡] (Select models)

▶ PIVOTING FRONT AXLE WITH RADIUS RODS

Robust front axle ensures that all four wheels hold their contact, enhancing comfort and quality of cut

NEW iCD+ Cutting System

Redesigned to deliver next-level performance, increased durability and superior results

Suspension platform system

The operator platform is suspended by a coil-over shock with five adjustable positions, optimizing operator comfort and increasing productivity

Hydro-Gear ZT-4400 transaxles

Dual-commercial transaxles with 8" cooling fans with a 3-year limited warranty[†]

Large fuel capacity

Generous 11 gallon fuel tank is centrally located for consistent balance, and the fuel filler neck is conveniently located on the side for easy filling

24" turf-friendly rear tires

Commercial-grade performance tires optimize stability and traction to deliver up to 12 mph of ground speed

Locking 4-position speed control

No tools are required to set the speed control bar, in increments of 1-2 mph, for smooth operation to max travel speed of 12 mph

* Power levels are stated gross horsepower at 3600 rpm per SAE J1940 as rated by Briggs & Stratton.

** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

‡ Cost savings based on oil maintenance with 100 hour interval versus Oil Guard System 500 hour service interval.

† See operator's manual or ferrismowers.com for complete warranty details. Refer to the engine operator's manual for engine warranty details.