

MOSS-AHD720-CM6S

Common Camera Placement Identified:

High resolution, 1.0 Megapixel, 720P, 12VDC 12 Leds, with Audio & smart IR-CUT



Description:


This is a high quality AHD (Analog High Definition) Color camera, using the latest CMOS technology, the camera can produce high definition image with little distortion.

Analog High Definition is a high video definition standard, through the coaxial cable, using the analog modulation technology to transfer progressive-scan HD Video signal. AHD system is same as traditional analog system, using common 75-3 coaxial cable to carry out as far as 500 meters HD video without any video signal loss.

Cautions:

- (a) In order to protect the camera, please avoid placing or using the camera under direct sunlight.
- (b) Please ensure that the input voltage range is within the specifications.
- (c) Please do not place the camera in a location with a temperature exceeding 50°C.
- (d) Do not attempt to service the camera by yourself. Please refer all services to qualified dealers.

Dimensions:




Packing list:

 Camera
 1

 Instruction manual
 1

 Hex-key
 2


 M4 self drilling screw
 3



Connection:



<u>Camera Module Orientation Matches Letter Orientation</u> Illustrated



(The front picture shown D orientation)

Specifications:

Model	MOSS-AHD720-CM6S
Pick up Device	1/4" CMOS Sensor AR0141
TV System	NTSC
Picture Elements	1280(H)*720(V)
Effective pixels	1.0M pixels
Day-night mode	External control (default) / Auto / color / black and white (OSD switching)
Infrared Spectrum	850nm
S/N Ratio	More Than 48 dB, (AGC Off)
Auto Gain Control	Auto
White Balance	Auto
Electronic Shutter	AUTO/ 1/50 (1/60) -1/100,000sec
Back Light Compensation	Auto
Infrared LED	12 LEDs
Infrared LED Range	10 m
Video output	1 Vp-p, 75ΩComposite,4 ways Din jack x1
Mirror	4 ways Din jack x1
Lens	Standard f2.1mm Fixed Megapixel Lens
Lens Mount	M12XP0.5mm Thread
Pan Adjusting	N/A
Tilt Adjusting	0-22°
!"#\$% &%%'()\$ '% '(*\$ +, -,(.\$	1min≈32MB
Power Supply	12V DC ±10%
Power Consumption	190mA
Dimensions(L x W x H)	100 x 65 x 68 mm
Net Weight	360 g
Weatherproof	IP65
Operating Temperature	-20°C to +50°C

^{*}Specifications are subject to change without prior notice.

 Input voltage exceeding the nominal rating by over +/-10% will cause abnormal operation.

Note: This camera needs to connect to MDVR or DVR that supports AHD (Analog High Definition) system.

4-MAN-MOSS-AHD720-CM6S REV. A

G.P.S. TRACKING, FLEET MANAGEMENT & MOBILE SURVEILLANCE SYSTEMS