



# *Roofing Product Reference Guide*



**SHINGLES**

---

**UNDERLAYMENT**

---

**ACCESSORIES**




# Designer Shingles Featuring Scotchgard™ Protector

For lasting protection against black streaks caused by algae, install shingles featuring the Atlas Lifetime\* Algae Resistance Limited Warranty.

## StormMaster® Slate

High Wind And Impact Resistant Shingles



Length: 22<sup>1</sup>/<sub>6</sub>" / 576.3 mm  
Width: 18<sup>1</sup>/<sub>2</sub>" / 469.9 mm  
Exposure: 8<sup>1</sup>/<sub>2</sub>" / 215.9 mm  
Shingles Per Bundle: 25



### 6 COLORS

Blackstone Slate  
Chalkstone Slate  
Emerald Slate  
Hearthstone Slate  
Pewter Slate  
Weathered Slate

### FEATURES

Scotchgard™ Protector  
130 mph Wind Limited Warranty\*\*  
FASTAC™ Double Sealant Lines  
Manufactured Using Core4™  
Enhanced Polymer Technology  
Class 4 Impact Resistance - UL 2218<sup>2</sup>  
Atlas Lifetime\* Algae Resistance  
Limited Warranty  
Lifetime Limited Warranty\*\*  
Atlas Signature Select® Eligible<sup>1</sup>


### ASTM

D7158, Class H Wind Resistance,  
Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance

### UL

2218, Class 4 Impact Resistance  
790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product  
Control Approved 




A Brand You  
Know And Trust  
**Scotchgard™ Protector**  
**25+** years of proven  
performance.



For maximum protection and warranty coverage,  
install an Atlas Signature Select® Roofing System with  
components designed and backed by an Atlas warranty.

## StormMaster® Shake

High Wind And Impact Resistant Shingles



Length: 42" / 1066.8 mm  
Width: 14" / 355.6 mm  
Exposure: 6" / 152.4 mm  
Shingles Per Bundle: 18-20



### 10 COLORS

#### Natural Expressions:

Chestnut  
Copper Canyon  
Majestic Shake  
Morning Harvest  
Silver Stone

#### Classic:

Black Shadow  
Hearthstone Gray  
Highland Brown  
Pewter  
Weathered Wood

### FEATURES

Scotchgard™ Protector  
Up To 150 mph Wind Limited Warranty\*\*  
FASTAC™ Double Sealant Lines  
Manufactured Using Core4™  
Enhanced Polymer Technology  
Class 4 Impact Resistance - UL 2218<sup>2</sup>  
Atlas Lifetime\* Algae Resistance  
Limited Warranty  
Lifetime Limited Warranty\*\*  
Atlas Signature Select® Eligible<sup>1</sup>


### ASTM

D7158, Class H Wind Resistance,  
Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance

### UL


2218, Class 4 Impact Resistance  
790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product  
Control Approved 

## Pinnacle® Pristine

High Performance Architectural Shingles



Length: 42" / 1066.8 mm  
Width: 14" / 355.6 mm  
Exposure: 6" / 152.4 mm  
Shingles Per Bundle: 18-20



### 19 COLORS

#### Natural Expressions:

Coastal Granite  
Copper Canyon  
Majestic Shake  
Morning Harvest  
Summer Storm

#### Classic:

Pristine Black  
Pristine Desert  
Pristine Hearthstone  
Pristine Heather  
Pristine Hickory  
Pristine Oyster  
Pristine Pewter  
Pristine Sienna  
Pristine Tan  
Pristine Weathered Wood

#### Special Order:

Pristine Green  
Pristine Pearl  
Pristine Sunset  
Pristine Weathered Shadow


### FEATURES

Scotchgard™ Protector  
130 mph Wind Limited Warranty\*\*  
FASTAC™ Double Sealant Lines  
Atlas Lifetime\* Algae Resistance  
Limited Warranty  
Lifetime Limited Warranty\*\*  
Atlas Signature Select® Eligible<sup>1</sup>


### ASTM

D7158, Class H Wind Resistance,  
Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance

### UL


790, Class A Fire Resistance   
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product  
Control Approved 

# Value Shingles

## ProLam<sup>®</sup> Architectural Shingles



Length: 42" / 1066.8 mm  
Width: 14" / 355.6 mm  
Exposure: 6" / 152.4 mm  
Shingles Per Bundle: 18-20



### 7 COLORS

Black Shadow  
Burnt Sienna  
Desert Shake  
Hearthstone Gray  
Heather  
Pewter  
Weathered Wood



### FEATURES

Up To 130 mph Wind Limited Warranty\*\*  
Algae Resistant Shingle  
Lifetime Limited Warranty\*\*  
3M Ceramic-Coated Granules

### ASTM

D7158, Class H Wind Resistance, Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance


### UL

790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product Control Approved

## Legend<sup>®</sup> Designer Fiberglass Shingles



Length: 36" / 914.4 mm  
Width: 12" / 304.8 mm  
Exposure: 5" / 127 mm  
Shingles Per Bundle: 26



### 5 COLORS

Black Shadow  
Desert Shake  
Hearthstone Gray  
Heatherblend  
Weathered Wood

### FEATURES

Scotchgard<sup>™</sup> Protector  
110 mph Wind Limited Warranty\*\*  
40-year Atlas Limited Warranty\*\*  
Atlas Signature Select<sup>®</sup> Eligible<sup>1</sup>

### ASTM

D7158, Class H Wind Resistance, Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance


### UL

790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product Control Approved

## GlassMaster<sup>®</sup> Performance Fiberglass Shingles



Length: 36" / 914.4 mm  
Width: 12" / 304.8 mm  
Exposure: 5" / 127 mm  
Shingles Per Bundle: 26



### 12 COLORS

Black Shadow  
Burnt Sienna  
Cool White  
Desert Shake  
Dove Gray  
Hearthstone Gray  
Heatherblend  
Oyster Shell  
Pewter  
Tan Mist  
Weathered Wood  
Woodland Green

### FEATURES

60 mph Wind Limited Warranty\*\*  
30-Year Limited Warranty\*\*  
Algae-Resistant Shingle  
3M Ceramic-Coated Granules  
Atlas Signature Select<sup>®</sup> Eligible<sup>1</sup>

### ASTM

D7158, Class H Wind Resistance, Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Type 1, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance


### UL

790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product Control Approved

## Tough-Glass<sup>®</sup> Original Fiberglass Shingles



Length: 36" / 914.4 mm  
Width: 12" / 304.8 mm  
Exposure: 5" / 127 mm  
Shingles Per Bundle: 26



### 2 COLORS

Black Shadow  
Weathered Wood

### FEATURES

60 mph Wind Limited Warranty\*\*  
20-Year Limited Warranty\*\*  
3M Ceramic-Coated Granules

### ASTM

D7158, Class H Wind Resistance, Passed at 150 mph  
D6381, Uplift Resistance  
D3018, Type 1  
D3161, Type 1, Class F, Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance

### UL

790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved – FL 16305  
Miami-Dade County Product Control Approved



### Dreaming of a home redesign?

Get creative with the Roof Inspiration Center, a suite of home design tools from Atlas. Whether you have 3 minutes or 30, your new look is just around the corner.


[AtlasRoofing.com/Roof-Inspiration](http://AtlasRoofing.com/Roof-Inspiration)

To provide homeowners the most accurate representation of color options, several photo scans and house shots were utilized in various lighting conditions. Variations in lighting illustrate the color gradients on asphalt shingle roofs.

Color blends vary from shingle to shingle. Before installation, consult with your contractor and request to view the actual shingles being installed on your roof to ensure confidence in your final color selection.


# Roof Shingle Accessories

## Pro-Cut® High Profile Hip & Ridge Shingles



Dimensions: 10" x 11½"  
Exposure: 8¼"  
Coverage: 20 Linear Feet  
Shingles Per Package: 30

## Pro-Cut® Hip & Ridge Shingles



Dimensions: 12" x 12"  
Exposure: 5 5/8"  
Coverage: 31 Linear Feet  
Shingles Per Package: 66



### COLORS

To match Atlas shingles

### FEATURES

Scotchgard™ Protector  
Manufactured Using SBS Asphalt  
Atlas Lifetime\* Algae Resistance  
Limited Warranty  
Lifetime Limited Warranty\*\*  
Atlas Signature Select® Eligible<sup>1</sup>

### CODES AND COMPLIANCES

Class A Fire Resistance (UL R21860)  
Wind Resistance (UL 997)  
CAN/CSA-A123.5-M90



### COLORS

To match Atlas shingles

### FEATURES

Scotchgard™ Protector  
Manufactured Using Core4™  
Enhanced Polymer Technology<sup>3</sup>  
Class 4 Impact Resistance – UL 2218<sup>2,3</sup>  
Atlas Lifetime\* Algae Resistance  
Limited Warranty  
Lifetime Limited Warranty\*\*  
Atlas Signature Select® Eligible<sup>1</sup>

### ASTM

D3018, Type 1  
D3161, Type 1, Class F,  
Tested at 110 mph  
D3462, As Manufactured  
E108, Class A Fire Resistance


### UL

790, Class A Fire Resistance  
2390, Class H Wind Resistance

### CODES AND COMPLIANCES

Meets AC438 Criteria  
CAN/CSA-A123.5-M90  
Florida Building Code Approved –  
FL 16305  
Miami-Dade County Product  
Control Approved

## Pro-Cut® Starter Shingles



## 6XR STARTER SHINGLE ROLL

Roll Dimensions: 7.2" x 33' 4"  
Exposure Limits: Up To 6"  
Per Roll: 33' 4"

## Universal 8.5x STARTER SHINGLES

Shingle Dimensions: 10 5/8" x 36"  
Exposure Limits: Up To 8 1/2"  
Per Bundle: 78 Linear Feet

## Universal 10x STARTER SHINGLES

Shingle Dimensions: 12" x 36"  
Exposure Limits: Up To 10"  
Per Bundle: 78 Linear Feet

# Premium Underlayments

## Synthetic

## Summit® 180 Premium Synthetic Underlayment



Length: 250'  
Width: 48"  
Square Per Roll Coverage: 10  
Coverage with 4" Lap: 917 sq. ft.

### CODES AND COMPLIANCES

AC 207, UV Exposure for 180 Days  
AC 207, Accelerated Aging  
ASTM E108, Fire Resistance  
ASTM D6757, Inorganic Shingle  
Underlayment Standard

### PERFORMANCE

#### CHARACTERISTICS EXCEED:

ASTM D4869, Type I, Type II, Type III,  
Type IV (Standard specification for  
asphalt-saturated felt), ASTM D226  
Type I & Type II  
UL 790, Fire Resistance  
UL Classified as a Prepared  
Roofing Accessory  
Florida Building Code Approved - FL 21350  
Miami-Dade County Product  
Control Approved

## Summit® 60 Synthetic Underlayment



Length: 250'  
Width: 48"  
Square Per Roll Coverage: 10  
Coverage with 4" Lap: 917 sq. ft.

### CODES AND COMPLIANCES

AC 207, UV Exposure for 60 Days  
AC 207, Accelerated Aging  
ASTM E108, Fire Resistance  
ASTM D6757, Inorganic Shingle  
Underlayment Standard

### PERFORMANCE

#### CHARACTERISTICS EXCEED:

ASTM D4869, Type I, Type II, Type III,  
Type IV (Standard specification for  
asphalt-saturated felt), ASTM D226  
Type I & Type II  
UL Classified as a Prepared  
Roofing Accessory  
Florida Building Code Approved - FL 21350

## Engineered Felt

## 30 Gorilla Guard® 30 Engineered Underlayment



Length: 141.5'  
Width: 36"  
Square Per Roll Coverage: 4  
Coverage with 2" Lap: 400 sq. ft.

### CODES AND COMPLIANCES

UL Classified as a Roofing Accessory  
ASTM D6757  
Florida Building Code Approved - FL 17322  
Meets Performance Characteristics of  
ASTM D4869 (#15 & #30 Standard) and  
ASTM D226 Type I

## 30 Gorilla Guard® Spec 30 Engineered Underlayment



Length: 72'  
Width: 36"  
Square Per Roll Coverage: 2  
Coverage with 2" Lap: 200 sq. ft.

### CODES AND COMPLIANCES

ASTM D4869, Type IV  
ASTM D226, Type II  
ASTM D6757  
Florida Building Code Approved - FL 16226  
Miami-Dade County Product  
Control Approved

\* In order to qualify for the Atlas Lifetime Algae Resistance Limited Warranty against black streaks caused by blue-green algae, installation must include Atlas Pro-Cut® Hip & Ridge shingles featuring Scotchgard™ Protector or Atlas Pro-Cut® High Profile Hip & Ridge shingles featuring Scotchgard™ Protector with Atlas shingles featuring Scotchgard™ Protector.

\*\* Refer to the Atlas Roofing Limited Shingle Warranty for all coverage requirements.

<sup>1</sup> Refer to the Atlas Signature Select® Limited Warranty for all system coverage requirements.

<sup>2</sup> UL 2218 for Class 4 Impact Resistance is applicable to product manufactured at the Ardmore, OK plant.

<sup>3</sup> Pro-Cut® Hip & Ridge manufactured in Hampton, GA is not made with modified asphalt and is not a Class 4 shingle.

<sup>4</sup> Helps resist the black streaks caused by algae.

Scotchgard and the Scotchgard Protector logo, including the plaid design and 3M logo, are all trademarks of 3M.

# SBS Peel & Stick Premium Underlayments



Length: 66.8'  
Width: 36"  
2 Square Roll Provides Approximately  
200 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Ice Dam and Metal Underlayment  
ICC-ES Report ER 1783  
Florida Building Code Approved - FL 17322  
Miami-Dade County Product  
Control Approved



Length: 72.1'  
Width: 36"  
2 Square Roll Provides Approximately  
216 sq. ft. of Material

## CODES AND COMPLIANCES

ASTM D1970, Standard Ice Dam Underlayment  
ICC-ES Report ER 1783  
Florida Building Code Approved - FL 17322  
Miami-Dade County Product  
Control Approved



Length: 65'  
Width: 36"  
1.95 Square Roll Provides Approximately  
195 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Standard Ice Dam Underlayment  
ICC-ES Report ER 1783  
Florida Building Code Approved - FL 17322  
Miami-Dade County Product  
Control Approved



Length: 33.3'  
Width: 36"  
1 Square Roll Provides Approximately  
100 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Standard Ice Dam Underlayment  
ICC-ES Report ER 1783  
Florida Building Code Approved - FL 17322  
Miami-Dade County Product  
Control Approved



Length: 65'  
Width: 36"  
1.95 Square Roll Provides Approximately  
195 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Standard Ice Dam Underlayment  
ICC-ES Report ER 1783



Length: 72'  
Width: 36"  
2 Square Roll Provides Approximately  
216 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Premium Ice Dam and Tile Underlayment  
Florida Building Code Approved - FL 17322  
Miami-Dade County Product  
Control Approved



Length: 66.8'  
Width: 36"  
2 Square Roll Provides Approximately  
200 sq. ft. of Material

## CODES AND COMPLIANCES

Underwriters Laboratories Class A and  
Class C Fire Rating – Based on Roof Covering  
ASTM D1970, Standard Ice Dam Underlayment  
Florida Building Code Approved - FL 17322



Length: 33.3' (1 sq.) 66.6' (2 sq.)  
Width: 36"

## CODES AND COMPLIANCES

ASTM D1970, Moisture Vapor Permeability  
ASTM D4869, Liquid Water Transmission

# Felt Underlayments

## #30 Organic Saturated Felt



Length: 72'  
Width: 36"  
Square Per Roll Coverage: 2  
Square Feet Per Roll: 216

## CODES AND COMPLIANCES

ASTM D4869, Type 1  
Florida Building Code Approved - FL 17322

## #15 Organic Saturated Felt



Length: 144'  
Width: 36"  
Square Per Roll Coverage: 4  
Square Feet Per Roll: 432

## CODES AND COMPLIANCES

ASTM D4869, Type 1  
Florida Building Code Approved - FL 17322



**AtlasRoofing.com**

#AtlasProtects

© Copyright 2020, Atlas Roofing Corporation ATL-205301-00 3/20