

SLIDING GLASS DOORS

CAMELOT[®]



SLIDING GLASS

FEATURES

OPTIONS

Our premium sliding glass door provides your home with an entryway that is beautiful, durable and energy-efficient for years to come.

BETTERVUE SCREEN

Extruded locking screen featuring Bettervue fiberglass screen wire

BETTER VENTILATION

2 position venting latch

TRANSOM**

fixed insulated glass unit mounted above door

SIDELITE**

fixed insulated glass unit mounted alongside door

DP-50 Rating Comes Standard*. *Only for 5 and 6 ft. doors

Fully-welded tempered insulated sliding glass door available in two or three panels, right or left slide. Nominal sizes are 5', 6', 8', 9'. 12' is available in four panels.

**The fully-welded transom and sidelite options are available as complimentary pieces.

ADDED STRENGTH

4" wide sash rails for beauty and added strength

TEMPERED GLASS

7/8" tempered insulated glass with optional Solarban 60 Low-E, or 1" internal blind glass with optional Cardinal's E270 Low-E.

COMFORT OF HANDLING

Contoured shape premier handle set

MULTI-POINT LOCK

Two lock positions with one turn of the key or thumbturn

EASY OPERATION

Heavy-duty adjustable rollers, up to 500lb


EASY GLIDE

Tempered aluminum sill track for easy glide



QUALIFICATIONS CRITERIA

Program Requirements for Windows, Doors, & Skylights: Version 6.0 (January 1, 2016)



Climate Zone	U-Factor ¹	SHGC ²
Northern	≤ 0.27	Any
N. Central	≤ 0.30	≤ 0.40
S. Central	≤ 0.30	≤ 0.25
Southern	≤ 0.40	≤ 0.25


¹ Btu/h ft² · °F ² Solar Heat Gain Coefficient

U-VALUES	Sliding Glass Door	Sidelite/Transom
Low-E/Argon Option*	0.30	0.27
Standard Clear	0.45	0.45


*For 7/8" IGs with SB60 Low-E glass.

GRIDS

(STYLE)



COLONIAL



QUEEN ANNE



DIAMOND*

(TYPE)



CONTOUR



FLAT



ELITE

COLOR

(STANDARD VINYL COLORS)



WHITE*



ALMOND*



COCOA (WHITE)

HARDWARE



White



Almond




Cocoa/Brass

White Int.

Satin Nickel

Bronze/White Int.

(Hardware standardly matches vinyl color.)



FACTORY MULLING

The sliding glass door and transom and/or sidelite can be chosen to be factory mulled together for added strength and customization.

BLINDS BETWEEN GLASS WITH LOW-E GLASS

Internal blinds are installed between two panes of glass which allow your blinds to be adjusted up/down and tilt with minimal effort using slid handles. This configuration keeps your blinds clean and prevents damage.




CUSTOM SIZING

Custom sizing is available in 1/4" intervals for custom fitting of your opening.



STAINLESS COASTAL HARDWARE PACKAGE

Replace door hardware (mortise lock, keeper, door rollers, screen wheels) to better withstand salt water weather conditions.



IMPACT CERTIFICATION

Produce your DP-50 door with impact certification, at a maximum size of 96"x96"



SIZE CHART

Minimum opening	59 3/4"	71"	71 3/4"	95 3/4"	107 3/4"	143 3/4"	143 3/4"
Frame	59 1/4"	70 1/2"	71 1/4"	95 1/4"	107 1/4"	143 1/4"	143 1/4"
12"					(4-Lite)		(3-Lite)
80"					(4-Lite)		(3-Lite)
79 1/2"					(4-Lite)		(3-Lite)
	5 ft.	6 ft.	8 ft.	9 ft.	12 ft.	12 ft.	

*For all orders, please allow a minimum of 1/2" clearance for the top and 1/4" clearance on both sides. *Right or Left handed is available; operating panel viewed from the inside.
*Continuous head and sill option available for sizing up to 107-1/4" 3-panel. 143-1/4" options shown are accomplished via factory mulls.

... AND WE BUILD WINDOWS.



215.535.7110 • 4280 Aramingo Avenue • Philadelphia, PA 19124-5007 • NBPwindows.com

Northeast Building Products Corp. and Camelot® Windows & Doors are registered trademarks. All Rights Reserved.



TOP 100
Manufacturers **Window & Door**

