



# ORIGINS

Electronic control valve  
by Aerus Origins™

***Treat Your Water. Take Care of Your Health.***

## WCF200

With a combination of both softening resin and activated carbon, the Origins Model WCF200 addresses a number of water quality issues in one device. Through ion exchange, calcium and magnesium is removed creating softened water for the benefit of both you and your homes' appliances. In addition, the reduction of chlorine, as well as many objectionable taste and odor characteristics are addressed by adsorption with coconut shell activated carbon. Using proven electronic controls and a robust ceramic disc valve, this hands-free system offers years of maintenance free operation.

## FEATURES

- Fully ported electronic valve affords fully automated, metered functionality
- Accommodates any type of plumbing
- Robust ion exchange resin for years of service-free operation
- Coconut shell activated carbon media eliminates both sediment and taste issues
- An innovative ceramic core control valve design for smooth, dependable operation

## BENEFITS

- Softened, iron free water from every faucet in your home
- Eliminates particulate such as sand, rust, and other sediment
- Reduction of chlorine and objectionable smells from odor causing organics
- Metered demand controls to reduce operating costs
- Better tasting water, coffee, tea, and other beverages made from tap water
- Significant reduction of soap and cleaning products cost



## SPECIFICATIONS

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| Product Information   | 00741 Model: WCF200                                                |
| Control Valve         | Fully automatic with metered flow initiation                       |
| Media Tank            | 12" x 52" (30.5 cm x 132.1 cm); rated to 600 psi; NSF Certified    |
| Coconut Shell Carbon  | 1 ft <sup>3</sup>                                                  |
| Exchange Resin        | 1 ft <sup>3</sup>                                                  |
| Brine Tank            | 16" x 33" (40.6 cm x 83.8 cm); holds up to 5 bags of softener salt |
| Service Flow Rate     | 8 GPM                                                              |
| Drain Flow Rate       | 4.8 GPM                                                            |
| Plumbing Connections  | In/Out up to 1" pipe size                                          |
| Operating Pressure    | Up to 125 psi                                                      |
| Operating Temperature | 34°F to 110°F (1.1 °C to 43.3 °C)                                  |

EXCLUSIVE ELECTRONIC DIGITAL CONTROL VALVE:

- Electronic back-lit display
- No gears to break
- Automatically calculates:
  - Usage
  - Capacity
  - Reserve volume
- Eliminates mechanical & cable
- Motor only runs during regeneration
- High flow rates for steady performance when multiple faucets are in use
- Knows how much water is used and when
- Simple set time of day and hardness



**Healthy Home Experts**

From 1924 through the turn of the century, we were Electrolux, the clear leader in home cleaning throughout North America. Now, we're Aerus, a new name for a new generation of products and services designed to help make your home a Healthy Home. All backed by performance so legendary, over 99.8% of our customers recommend Aerus to their friends and family.

Honored by the Smithsonian  
Trusted by Millions of Homes



For more information, please contact:

Contact Name: \_\_\_\_\_

Email: \_\_\_\_\_

Phone Number: \_\_\_\_\_

Website: \_\_\_\_\_

Electrolux and Lux are registered trademarks of Aktiebolaget Electrolux and are licensed for use by Aerus LLC and its affiliates. Aerus and all derivative forms are trademarks of Aerus Concepts, L.P.